### A REPORT ON THE PARTICULATE EMISSIONS PERFORMANCE OF MASONRY HEATERS – DEFINTION, DATA, ANALYSIS AND RECOMMENDATIONS

Prepared for: The Masonry Heater Caucus of the Hearth, Patio and Barbecue Association

Prepared by: Robert Ferguson

Ferguson, Andors & Company

P.O. Box 678

South Royalton, VT 05068

Date:

February 13, 2008

The scope of this report is to provide the U. S. Environmental Protection Agency with chronologically organized information about the particulate emissions performance of masonry heaters as a defined product class and to provide conclusions and recommendations based on that information.

# A REPORT ON THE PARTICULATE EMISSIONS PERFORMANCE OF MASONRY HEATERS February 13, 2008

### Table of Contents

Introduction	3
Background	3
Definition	5
Data Summary	5
Conclusions	7
Recommendations	7
Attachment 1: Excerpt from Federal Register (Footnote 1)	8
Attachment 2: Best Available Control Measures Document Excerpts (Footnote 2).	9
Attachment 3: Renner Memo (Footnote 3)	11
Attachment 4: McCrillis Memo Excerpts (Footnote 4)	14
Attachment 5: ASTM E1602-03	19
Attachment 6: Test Report Summary Table	28
Attachment 7: Referenced Report Bibliography	29
Attachments 8 - 21: Referenced Report Cover Pages and Excernts	21

#### Introduction

This White Paper is submitted by the Masonry Heater Caucus of the Hearth, Patio and Barbecue Association to support its request that the Office of Air Quality Planning and Standards (OAQPS) recognize that Masonry Heaters are a class of solid fuel heating devices that are inherently clean-burning and can be a viable emissions control option in PM-impacted areas. The White Paper has five parts:

- Background
  - Provides relevant background information on regulatory status, numbers installed annually, data sources, etc.
- Definition
  - Defines what comprises a clean-burning masonry heater including a list of critical features.
- Data
  - o Summarizes the available North American emissions performance data.
- Conclusions
  - o Summarizes our conclusions on emissions performance.
- Recommendations
  - A section containing our recommendations that includes procedures that can be used to provide assurances that masonry heaters built in the field include the critical elements identified in the definition of clean-burning masonry heater.

#### Background

Modern masonry heater designs originated in Europe and those designs have been in use for many decades, if not centuries. While masonry heaters are installed in relatively large numbers across Europe, they represent only a small niche in the solid-fuel burning market in the United States. Masonry heaters are site-built, often by individual masons, making it hard to provide a precise number of installed units. The Masonry Heater Caucus estimates that between 600 and 1,000 masonry heaters are installed in North America each year. This represents only a fractional percentage of all solid-fuel burning appliance sales and installations.

EPA's wood stove New Source Performance Standard (NSPS), 40 CFR Part 60, Subpart AAA, specifically exempts masonry heaters because the Regulatory Negotiation Committee recognized that they are inherently clean-burning due to their high burn rates and air-rich characteristics. This is explained in the preamble to the proposed regulations<sup>1</sup> as follows: "The 800 kg cutoff was established as an easy means of excluding

<sup>&</sup>lt;sup>1</sup> Federal Register/Vol. 53, No. 38/February 26, 1988/Rules and Regulations/Page 5864. See Attachment 1.

high mass fast-burn wood-burning appliances known as "Russian stoves" or "European tile stoves." These devices typically operate at hot, fast burn rates and cannot be damped. It is also likely that they are incapable of meeting the 5 kg/hr minimum burn rate. The intent of the committee was to exempt from the standards these appliances which rely on clean-burning air-rich conditions and which have high combustion efficiencies."

Notwithstanding EPA's clear determination in the NSPS rulemaking that masonry heaters are inherently clean-burning, because of their high burn rates and air-rich characteristics, masonry heaters have had a difficult time getting accepted by SIP planners as viable control options for PM-impacted areas. In some jurisdictions, only NSPS-certified wood stoves have been allowed. While the intent may have been to eliminate "loop-hole" products as a means of improving air quality, the result for some product classes, including masonry heaters, has been to effectively ban a clean-burning alternative. Other areas have followed EPA's RACM/BACM guidance<sup>2</sup> and allowed NSPS-certified appliances, along with other appliances that have been shown to be "equivalent." [See also Renner memo<sup>3</sup>.] However, these equivalency provisions, although written with good intent, are flawed in concept. The NSPS emission limits were based on Best Demonstrated Technology (BDT) for traditional wood-burning stoves and inserts and were supported with significant data from the Oregon woodstove certification program. These levels do not translate to appliances employing different technologies and, therefore, with different BDT. Masonry heaters are not designed nor do they operate like NSPS certified stoves or inserts. Moreover, the very different operating profiles for masonry heaters compared to woodstoves present difficult issues when attempting to make "equivalency" findings. The fuel load in a masonry heater is fully-consumed in a short period of time. This heats a large mass of refractory, which in turn discharges the stored heat over many hours. Woodstoves are also batch loaded, but the heat is delivered as the fuel load is consumed. The length of the burn depends on how the operator sets the air controls. When comparing emissions performance on a gram/hr basis, the masonry heater emissions must be averaged over the period of time that useful heat is being provided to the home in order to compare them with woodstoves on an "apples to apples" basis. Finally, the fact that air quality planning agencies frequently require costly case-by-case showings of "equivalency" has been an additional, significant obstacle to masonry heater builders.

We are presenting the results of masonry heater testing that has been conducted in North America, but it is important to recognize that considerable testing has also been conducted in Europe and that testing corroborates the clean-burning performance of masonry heaters as a class of products.

<sup>&</sup>lt;sup>2</sup> Technical Information Document for Residential Wood Combustion Best Available Control Measures, U. S. Environmental Protection Agency, Office of Air and Radiation, Office of Air Quality Planning and Standards, Research Triangle Park, NC, September 1992. See Attachment 2.

<sup>&</sup>lt;sup>3</sup> Memo: F. H. Renner to Chief, Air Branch, Regions I – X, September 23, 1991, Interpretation of EPA's Guidance for Residential Wood Combustion Emission Control Measures. See Attachment 3.

#### Definition

It is also necessary to establish a way to determine what masonry heater designs should qualify for recognition in that class and for that the following definition is proposed.

"A masonry heater is a site-built or site-assembled, solid-fueled heating device constructed mainly of masonry materials or soapstone in which the heat from intermittent fires burned rapidly in its firebox is stored in its massive structure for slow release to the building. It has an interior construction consisting of a firebox and heat exchange channels built from refractory components."

Specifically, a masonry heater has the following characteristics:

- Site-built or site-assembled.
- A mass of at least 800 kg. (1760 lbs.).
- Tight-fitting fuel loading doors that are closed during the burn cycle,
- An overall average wall thickness not exceeding 250 mm (10 in.).
- Under normal operating conditions, the external surface of the masonry heater, except immediately surrounding the fuel loading door(s), does not exceed 110 C. (230 F.).
- The gas path through the internal heat exchange channels downstream of the firebox includes at least one 180-degree change in flow direction, usually downward, before entering the chimney.
- The length of the shortest single path from the firebox exit to the chimney entrance is at least twice the largest firebox dimension.
- A combustion air control that is designed to provide a high-fire burn rate only.
- A combustion air introduction system that directs the majority of the combustion air to the area in the firebox that is at or above the level of the fire.
- Constructed or installed by qualified masonry heater builders.

ASTM E-1602 "Standard Guide for Construction of Solid Fuel Burning Masonry Heaters" provides design and construction information for the range of masonry heaters most commonly built in the United States and can be used as the basis for determining whether a particular design qualifies for recognition as a masonry heater. A copy for reference purposes only is included as Attachment 5.

#### **Data**

A table showing the reports from testing in North America that provides data relevant to types of masonry heaters that meet the above definition is included as Attachment 6. The table includes a brief description of the test parameters and the average emission results. The data comprises the results from research studies, test method development efforts, and testing for certification to state masonry heater rules. The average particulate

performance is presented as emission factors (grams of particulate per kilogram of fuel burned). This format provides the best way to compare emissions from high-burn-rate, high-combustion-efficiency, intermittently-fired appliances. Emission rates, when available in the reports, have also been provided. However, as was briefly discussed in the Background section, emission rates (grams of particulate per hour) can be deceiving when evaluating intermittently fired high-mass appliances. One or two fires that last only a few hours can provide heat for a full twenty-four hour period. Emission rates should therefore be normalized over the period of time that heat is being provided by the masonry heater if they are to be used to compare different appliance types. The emission rates we are reporting here may not have been calculated using the same procedures in each case. Some values have been normalized, some have not. These differences should be taken into consideration when comparing individual values. We have also included ranges for data, as well as results from individual heaters when available in the reports.

The data that we are presenting represents all data from masonry heater testing in North America that we have been able to obtain with the exception of data from a test series conducted on four products from one manufacturer<sup>4</sup>. Please note that some additional reports have been issued that address sub-sets of testing results from the reports we have cited. Those reports have not been included if their data are contained within the cited reports. The table also includes a reference to the AP-42 emission factor for masonry heaters. Full references for each cited report are included in Attachment 7.

Report cover pages and extracted summaries or excerpts from the reports, when available, are included in Attachments 8 - 21. Copies of the full reports can be made available upon request.

Reference C (Attachment 10) is the report on the field testing of five heaters that represent a cross-section of the masonry heater designs that were being built across the country. This study from 1991-1992 was funded by Masonry Heater Association members. Ultimately, EPA was approached and agreed to monitor and audit this test program. In an EPA memorandum<sup>5</sup>, Dr. Robert C. McCrillis presents his evaluation of the test results from the masonry heater test program. These results (which covered a broad range of heater designs) were used by EPA to calculate the 2.8 g/kg emission factor for masonry heaters that is listed in EPA's AP-42 document "Emission Factors from Residential Wood Combustion".

<sup>&</sup>lt;sup>4</sup> These data were excluded because the tests were not conducted following a masonry heater test protocol but were instead generated using a fueling and operating protocol for factory-built fireplaces.

Memo: R. C. McCrillis to D. Mobley, May 8, 1992, Masonry Heater Field Performance Data. See Attachment 4.

#### Conclusions

The test data support previous conclusions regarding the particulate emission performance of masonry heaters as a class and further defined as those designs that meet the criteria outlined earlier in this paper. Using a variety of test procedures, fueling protocols and fuel types, emission measurement methodologies, laboratory and in-situ measurements, the resultant average particulate emissions have ranged from 1.4 to 5.8 grams of particulate per kilogram of fuel burned. The average of the averages for this data is 2.9 g/kg. Again, the current AP-42 emission factor for masonry heaters is 2.8 g/kg. Note: We have not included the emission results for the Russian Heater cited in Reference B (Attachment 9). This heater was constructed by a mason inexperienced and untrained in masonry heater construction and the emission performance is considered as an outlier when compared to all other available data.

The low average particulate emissions from masonry heaters combined with the small number of annual installations justifies allowing masonry heater installations to continue without imposing undue burdens on the installers of these appliances. The cost associated with testing individual masonry heaters is simply prohibitive and does not represent a needed expenditure to protect air quality. Another means of satisfying air quality regulators is appropriate in this case.

#### Recommendations

Masonry heaters as a class should be accepted by EPA as clean-burning and EPA should give the appropriate guidance, in the form of a letter from the Office of Air Quality Planning and Standards, to state, local and tribal air quality regulators. That letter should recommend allowance of the installation and operation of qualified masonry heaters in PM-impacted areas as a viable strategy for PM reduction from Residential Wood Combustion (RWC). We suggest that the current AP-42 emission factor of 2.8 g/kg continues to be representative of the expected performance of masonry heaters as a class.

Qualified masonry heaters are defined as those in conformance with the masonry heater definition included in this paper.

Conformance with the specified masonry heater design parameters should be confirmed and documented by an independent third party laboratory for each masonry heater design. This would be an engineering evaluation based on design drawings provided by the masonry heater builder or manufacturer. The conformance report would be applicable to each heater that is installed in accordance with the conforming design. Additional affirmations by the masonry heater installer or builder that the design as built in the field is in conformance with the design drawings could be considered if needed.

### Attachment 1: Reference 1 - Excerpt from Federal Register

#### 5864 Federal Register / Vol. 53. No. 38 / Friday, February 26, 1988 / Rules and Regulations

firebox. RPA believes that it may still be possible for circumvention to occur. In such cases, however, it would be the consumer rather than the fireplace manufacturer who would be held accountable for making an affected facility. For example, if a homeowner installs an enclosure on his new fireplace and if this enclosure results in the facility meeting the four criteria that define a "wood heater," this homeowner has "manufactured" an affected facility. As noted below, homemade or handbuilt wood heaters are not exempt from this regulation.

As explained on page 4959 of the proposal preamble, the standards would apply to homemade woodstoves. One commenter stated that homemade woodstoves should be exempt from this regulation because homemade woodstoves are used primarily by the paor to provide inexpensive heat. Several other commenters favored the regulation of these appliances because of the relatively large number of such stoves, their impact on the environment, the potential for future circumvention if they are not controlled, and the potential sales that will be lost by manufacturers of wood heaters who have incurred the additional expense of complying with the regulation.

In response to the comment that homemade stoves should be exempt because they provide inexpensive heat for the poor. EPA believes that although the initial cost of a homemade stove may be less then a mass-produced manufactured woodstove, because it is assembled by the homeowner with some homeowner-supplied parts, it may likely be less durable, less efficient, and less safe—all of which may make it more expensive in the long run. Even if homemade stoves were to have lower life cycle costs, the lowered costs would not outweigh the environmental costs of exempting them from the standards. Finally, it should be noted that for those who cannot afford the initial costs of a new certified wood heater, this regulation does not restrict the sale of second hand stoves. The second hand stove market is a major source of inexpensive wood heating appliances.

The EPA agrees with the commenters affirming that kit stoves be regulated. One estimate indicates that homemade wood heaters comprise 5 percent of the market. Most of these are believed to be kit stoves. A kit stove is a type of wood heater that someone other than the commercial manufacturer completes or alters in a way as suggested by the manufacturer. A kit stove may or may not include all of the components necessary to construct the appliance.

but does include plans, designs, and assorted hardware (e.g., door, legs, flue pipe fittings). Often, the consumer supplies a steel drum which becomes the lirebox for the stove.

The EPA believes that manufacturers of kit stoves should be subject to the certification requirements as are the manufacturers of fully assembled wood heaters. Therefore, EPA is requiring that kit stove manufacturers have their designs certified. For those designs that are certified, the kit stove manufacturer would include in the kit any necessary hardware for assembling the emission controls (e.g., a catalytic combustor and associated equipment such as flown impingement shields and a temperature monitoring port), appropriate temporary and parmanent labels, and the owner's menual.

Because some of the fabrication of the wood heater occurs at the retail or consumer level, EPA requires that kit stove manufacturers submit a kit, rather than a fully assembled wood heater, to the accredited taboratory for certification testing. To approximate more closely the quality of fabrication that occurs among consumers, a laboratory technician, using only the instructions and designs available in the kit, would construct a wood heater using the materials in the kit and the type of firebox (e.g., sizes and quality of steel drum) specified in the instructions. If the instructions allow the consumer to substitute different components (e.g., different sized steel drums), each variation that could affect emissions would constitute a different model and require asparate certification.

The EPA is aware of at least one manufacturer of wood heater kits who sells catelytic combustors es an accessory. This same manufacturer has his stove designs sefety tested and provides labels indicating compilance with the U.S. Consumer Product Safety Commission safety testing requirements. Therefore, the approach described about would not represent a significant departure from existing practice. As suggested in the proposal preemble, in view of the emissions impact and the potential for circumvention if kit stoves are exempt from this regulation. EPA believes it is reasonable that kit stoves be covered by the regulation and that the manufacturers of the kits be responsible for having their designs cartified.

A commenter asked for clarification of the applicability of the standards to so-called "Russian stoves" or "Europear tile stoves."

The 800 kg cutoff was established as an easy means of excluding the high-

mass fast-burn wood-burning appliances known as "Russian stoves" or "European tile stoves." These devices typically operate at hot, fast burn rates and cannot be damped, it is also likely that they are incapable of meeting the 5 kg/hr minimum burn rate. The intent of the committee was to exempt from the standards these appliances which rely on clean-burning air-rich conditions and which have high combustion sfliciencies. It should be noted, however, the exclusion does not apply to appliances which exceed the 800 kg threshold only because of mesonry or other materials which are not sold by the manufecturer as integral parts of the appliance.

Two manufacturers of wood-fired cookstoves requested an exemption from the standards for these appliance types because the design principles for coom heaters and cookstoves were significantly different and because cookstoves comprise a very small fraction of the wood heater market.

The EPA agrees with the commenters who recommend excluding cookstoves. The operational characteristics of cookstoyes have not been shown to be compatible with the demonstrated technologies analyzed in this rulemaking. Also, the number of cookstoves is very small relative to all other wood heaters. Therefore, the promulgated standards exempt promusacea standards exemps cookstoves and include the definition of "cookstove" recommended by the WHA, with one modification as noted below. The design features necessary to be defined as a cookstove include: [1] An oven with an oven rack; (2) a mechanism for measuring the temperature in the oven; (3) a flame path which is routed around the oven: (4) a which is routed around the over, (4) a shaker gratet (5) an ash pan; (6) an ash clean-out door below the over; and (7) the absence of a fan and/or heat channels to dissipate heat from the appliance. The final standards include one modification not recommended by industry. To qualify, the appliance must have a minimum oven size of 0.028 cubic meters (1.0 cubic foot). This is smaller than the oven sizes of bona fide cookstoves currently on the market, but large enough to discourage circumvention of the standards by simply adding a small cavity and catting

One commenter asked whether a company that produced fewer than 2.000 stoves per year could purchase and produce a stove design from a large manufacturer and still be entitled to the 1-year exemption as a small manufacturer. This same commenter asked whether a qualifying small.

# A REPORT ON THE PARTICULATE EMISSIONS PERFORMANCE OF MASONRY HEATERS February 13, 2008

Attachment 2: Reference 2 - Cover page

Houch

EPA-450/2-92-002

TECHNICAL THEORMATION DOCUMENT FOR RESIDENTIAL WOOD COMBUSTION BEST AVAILABLE CONTROL MEASURES

U.S. Environmental Protection Agency Office of Air and Radiation Office of Air Quality Planning and Standards Research Triangle Park, North Carolina 27711

September 1992.



#### Attachment 2: Reference 2 - Excerpt

2.4 ALL NEW WOOD STOVE INSTALLATIONS<sup>3</sup> EPA-CERTIFIED, PHASE II STOVES OR EQUIVALENT

This integral measure recommends that stoves not be allowed to be installed which are (1) not certified by EPA to Phase II emission limits or (2) cannot document (through "in-home" field testing data) emissions equivalent to or less than "in-home" field test emissions of RPA-certified Phase II stoves.4 The intent of this requirement is to prevent the sale or resale and installation of non-EPA-certified stoves and the resale and installation of used EPA-certified Phase I stoves. The program should require that when homeowners intend to install a new or used wood stove, they file a form with the implementing or lead planning agency and swear in an affidavit that the stove is EPA-certified to Phase II emission limits. The implementing or lead planning agency should be responsible for processing the forms and affidavits and checking the brand name of the proposed stove installation against a list of EPA-certified, Phase II stoves (and their equivalents). Properly trained and qualified inspection personnel should conduct random surveys of stoves in homes to confirm compliance.

The implementing or lead planning agency should make the public aware of the requirement for stove certification, the

<sup>&</sup>lt;sup>3</sup>New installations should include both "brand-new" stoves and fireplaces and "new-used" units (i.e., newly purchased units that are not "brand-new").

<sup>4</sup>see memorandum clarifying nature of RWC guidance and describing procedure for entities seeking emission reduction credit for RWC devices not certified by EPA but which can demonstrate comparable or lower emissions through field testing. Process includes consultation with EPA's Office of Research and Development on appropriate in-use testing methods and procedures (Ref. 1). For example, EPA has recently reviewed in-home field data for certain masonry stoves tested during the 1991/92 heating season and has accepted the resultant emissions data for use in SIP-related activities (Ref. 2).

#### Attachment 3: Reference 3 - Renner Memo

	12/18/1	991 12:53 0/4/1 Environmental Su	ics.	503 526 2085 P.4	<b>0</b> 2
ويعين برورون المتلاء		19123 NHA JOHN CROUCH 203-278-36		2-2-2 <b>-2-2-2-2-2-2-2-2-2-2-2-2-2-2-2-2-</b>	Hart and assembly
4.2	1 1	19169 NUM TANA CHOREN SOS-STONES	19 D	CONTRACTOR MARINA	173
	ail Diverge		Post-It™ brend fat	x transmilial memb 7571	10101000 1/ 3
<b>3</b>	<b>₽</b> (4	UNITED STATES ENVIRONMEN	To SKID		ter
1		Office of Air Quality Plan Research Triangle Park, N	Co.	Ço.	
- Th.	AL PAGISTRA	and the second s	Dept	Priorie P	
			PAL S	Park.	Creamina Cr
				The same of	· · · · •
		September 23,	1991		
	•			's first the thirty	
		•		प्रकारण क्षेत्र	*
	*				
	MEMORANDU	R		(१५० हेन्स्टर सम्बद्धाः	e e e e e e e e e e e e e e e e e e e
is .	SUBJECT:	Interpretation of EPA's G	sidance for	Regidential Wo	di sasaay <del>ida</del> -
	QQDDLC11	Combustion Emission Contro			
			To	مستنفلته الراء	
	FROM:	Frad H. Renner, Jr., Actin SO <sub>2</sub> /Particulate Matter Pro	ng Chief (T	on, AOMD (MD-	53
			edrame watt	walker all	10 の意義
4 .	TOI	Chief, Air Branch		A substitution of the same	1
	r :	Regions I-X		i indicata incere	minute rations
	•			· · · · · · · · · · · · · · · · · · ·	
		eptember 1969, the U.S. Bo			
		ued guidance for controllin			
		al wood combustion (RWC) is for Residential Wood Combus			ADTICE:

In September 1989, the U.S. Environmental Protection Agency (EPA) issued guidance for controlling wood smoke emissions from residential wood combustion (RWC) in a document entitled Guidance Document for Residential Wood Combustion Emission Control Messures (EPA-450/2-89-015). The document was issued as a recommendation to State and local agencies developing wood smoke control programs and not to prevent such agencies from considering other wood smoke control devices or measures not discussed in the document. However, it has been brought to EPA's attention that, despite its purpose, the guidance has in some cases been construed as restrictive and exclusionary in mature. The purpose of this memorandum is to clarify EPA's intent behind issuing this guidance and explain what documentation EPA expects in evaluating control measures discussed and not discussed in the guidance.

The nonexclusionary nature of the guidance document is embodied in EPA's policy regarding RWC emission reduction credits as explained in Chapter 1.0 of the guidance document. To reiterate, the emission reduction credits recommended in Appendix F of the document are only suggested and should thus be considered starting points in assessing the effectiveness of RWC control programs and regulations. Any application for credit in a State implementation plan (SIP) must be accompanied by a justification in the implementing agency's specific program or regulation. For instance, for a mandatory curtailment program to receive a 50 percent wood stove credit, it should contain documentation in the SIP that the implementing agency has addressed each of the elements described in Table 5-9 of the document. All credit applications in SIP's are, of course, subject to EPA review to ensure the credit level is justified.

Page 11 of 72

12/18/1991 12:54 OMNI Environmental Suos.

503 526 2085 P.03

1 2

2

In their SIP's, State and local agencies can also request credit greater than that recommended in the document, as well as credit for measures not included in the document. Contrary to how the RWC guidance document may, in some cases, be interpreted, EPA will consider well-supported requests for credit for wood-burning devices not listed in Table 3-1 and Appendix F of the document. Merely because a wood-burning device is not EPA-certified does not mean it does not marit emission reduction credit and, hence, statum as a device that burns more cleanly than a conventional wood stove. To obtain credit, however, proponents for such devices must provide justification for credit to be granted in the same manner as the davices currently listed in the guidance document (e.g., EPA-certified Phase II cordwood and pellet stoves), as described below.

The suggested credits currently in the guidance document for the conversion of conventional wood stoves to EPA-certified catalytic, noncatalytic, and pellet stoves are based on field test data documenting the emissions reductions associated with the different advanced wood-burning technologies. Therefore, if SIP credit is sought for conversion to wood heaters not listed in the guidance document (including wood heaters determined to be "not affected" by EPA's wood heater new source performance standard definition (see 53 Foderal Register February 26, 1988) and hence exempt], the request should be accompanied by a justification based on emission reductions documented through "in-home" field testing (versus laboratory testing). The EPA recommends that the field testing employ an emissions sampling and data-gathering technique that is reviewed by EPA prior to the start of testing.

If EPA finds that field test data indicate a wood-burning device not currently listed in the guidance document is clean burning relative to conventional stoves and, therefore, warrants emission reduction credit, depending on its emissions performance, that stove may be afforded status similar to that of an EPA-certified stove with demonstrated emissions significantly lower than that of conventional stoves. That is, EPA will approve control strategies under SIP's to the extent of demonstrated emission reduction credits for such devices.

In-use testing to establish emission reduction potential should be conducted in accordance with valid procedures established in consultation with EPA's Air and Energy Engineering Research Laboratory within the Office of Research and Development. Should you be contacted by an air pollution control agency or by any other entity seeking credit for devices that have not already been subject to in-use testing, please refer them to Robert McCrillis at 919/541-2733.

593 526 2965 P.84 i2/18/1991 12:55 DMN1 Environmental Svcs. If you have any questions regarding this clarification please contact Chris Stoneman (FTS 629-0823). Attachment Bob Lebens, SSCD Vickie Patton, OGC Bob McCrillis, ORD Gwen Jacobs, AQMD Chris Stonemen, AQMD Eric Gineburg, AQMD PM-10 Contacts, Regions I-X aa:

#### A REPORT ON THE PARTICULATE EMISSIONS PERFORMANCE OF MASONRY HEATERS February 13, 2008

### Attachment 4: Reference 4 – McCrillis Memo Excerpts

108/03/93 12:35 **23**919 541 2157 EPA/AEERL/RTP, NC

**MO01** 



#### UNITED STATES ENVIRONMENTAL PROTECTION AGENCY OFFICE OF RESEARCH AND DEVELOPMENT AIR AND ENERGY ENGINEERING RESEARCH LABORATORY RESEARCH TRIANGLE PARK, NORTH CAROLINA 27711

DATE:

May 5, 1982

SUBJECT: Masonry Wood Heater Field Performance Data

FROM:

Robert C. McCrillis Organics Centrol Branch

TO:

David Mobley

Chief, Emission Inventory Branch (MD-14)

**QAQPS** 

THRU:

Wade Ponder

Chief, Organics Control Branch (MD-61)

THANGALT

This memo transmits to you my evaluation of the test results obtained during the 1991-92 winter on masonry wood heaters. Masonry wood heaters are exempt from EPA regulation under the wood Masonry wood heaters are exempt from EFA regulation under the wood heater NSPS because their weight exceeds 800 kg. Some are also exempt because their air to fuel ratio exceeds 35:1. EPA established a procedure wherein manufacturers of exempt wood burning devices could have their products tested in the field using methods acceptable to EPA. EPA then would publish the results for the state and local regulatory agencies use in preparing SIPs.

Four masonry heater manufacturers and one factory built fireplace manufacturer decided to take advantage of this opportunity and contracted to have their devices field tested this past winter. I was asked by OAQPS to review the test procedures used and determine if they were, in my judgement, acceptable to EPA. The masonry heaters were tested by OMNI Environmental Services, Inc. and the fireplace by Virginia Polytechnic Institute and State University.

In my judgement, the procedures used by OMNI were acceptable In my judgement, the procedures used by OMNI were acceptable to EFA. To provide an independent review of their procedures, I asked Judy Ford to provide QA oversight as if this were an AEERL-funded project. Three audits were performed by Research Triangle Institute (RTI): Laboratory Technical Systems, Laboratory Performance Evaluation, and Field Technical Systems and Performance Evaluation. All three audits received the rating "acceptable with qualifications". This rating is next to the highest (best)

<sup>1.</sup> Memo, F.H. Renner to Chief, Air Branch, Regions I-X, September 23, 1991.

end-03/93 12:38 25939 541 2157

EPA ABERL RIT N

possible rating. This rating means?:

"Minimum criteria are satisfied and good data quality seems likely; qualifications on the possible limitations of the data are noted and some corrective actions may be recommended. The recommendations may be implemented at the Project Officer's discretion."

Several of the more significant recommendations were implemented and are reflected in the results in the following table.

Masonry heater field tost data - 1991-92 heating season.

Heater Brand	PM10 M5H g/kg	Burnrate kg/hr	ā\kā Çō	VOC g/kg	Efficiency	Wood Species/ % moisture
Grundofen Crown Royal 2006 BioFire 4X3 Tolikivi KTU2100	1.62 2.06 2.20 6.39	0.95	83.00 69,10 72.00 107.00	0,37	65.40 54.00	DF/20% Alder/20% DF/19% DF/20%

The PM10 values have been converted to EPA Method 5% (M5%) equivalents. Under wood species, DF means douglas fir.

The procedures used by VPI were also acceptable to EPA, in my judgement. RTI is in the process of reviewing VPI's input. AEERL performed extensive audits of VPI during the 1989-90 heating season tests in Crested Butte and found their procedures acceptable. Since VPI used basically the same procedures and the same field personnel this winter, I feel confident in their results. As far as the fireplace results are concerned, however, all this is mute since the emission rates were much higher than hoped so the manufacturer (Majestic) has asked that they not be disclosed. AEERL is currently testing one of Majestic's "low emission" fireplaces in our laboratory. To date, results look quite good. I do not know why the field data came out high except that Majestic told me the homeowner operated it at a very low burnrate. This fireplace incorporates the secondary combustion technology in the better noncatalytic woodstoves; if not operated hot enough, however, they produce high emissions. At the appropriate burnrate, the fireplace consumes wood at a rate in the range of 4-6 kg/hr. Perhaps the homeowner did not want to use wood at that rate.

I am attaching copies of the individual masonry heater test reports. I received these from the manufacturers and there was no mention of the reports being confidential.

cc (with attachments): Chris Stoneman (MD-15) Michael Hamlin (MD-14)

AEERL Quality Assurance Procedures Manual for Project Officers.

QG:03:83 12:51 **23**919 541 215

Table 1. Summary of conventional fireplace data.

EPA-ABERL-RTP.NC

**12**0027003

92-118.06

HOUSE AND SHOW	740 44	EGATA	50,001	200.00	1		
SAMPLE DATES:	1417	90	-027	200	1,000		
	1320791	20,53,505	SASSA	2/23/01	3/10/91		
PIREPLACE TYPE	8	-800	CON	MODENED.	60 FG		
. 1	VENTIONAL	TENTIONAL	<b>JENDUNDA</b>	4UMFORD		AVERACES	-
FUEL TYPE:	5. F.R.	O, FIR	٠. ٦	O. FIR	HIL C		
FUEL MOISTORE:	20% MESST	TEKNIK ANDI	20% MOGST	25 FOR 1	2:5 MOIST		
TOTAL STOYE BURNAG HOURS.	73.85	52.0F	24.67	24,74	28.92	67.3	TOTAL STOVE BOOKING HOLDS
X OF TIME FIREPLACE BURRED.	4,07	15,16	3.83	23.4B	46.89	R	A CHAME HREPLACE MINARCA
AVE, STACK TEMPOEGREES C)	₹ -	2	ŧ	38	5	ž	AVE. STACK THAPMENARDS
AVE OXYGEN MOTACKS BEGICL	20.15	\$ 62	10.50	N	100	20.30	AVE SYMPTON CONTRACTOR OF STATEMENT
AVE, DXMSEN % (DAG)*	202	20.4	203	¥Ď.	10.7	R	AVE.OXYGEN & (BAG) =
TOTAL WOOD USED (WET light	Not determined	2,2	52.7			38.6	TOTAL WOOD USED METABLE
WOOD MOISTURE (DRY BASIS 19)=	183		10.0			10.6	ACOD MONTHER THAN BLOCK
AMES FLOW PATE (L./min)-	1.029	0.844	1,025		•	0.90	AWES FLOW MATER A JOHNS
LENGTH OF SAMPLING CYCLE (mh)=	~	N	r		Ħ	250	LENGTH OF SAMPLING CYCLP (min)::
AVERAGE CO % (BAG)=	0.078	0.050	DHO'O	0.0050	6,070	0.055	AVERAGE CONT. CHACLE
AVERAGE COZ % (BAG)	Ġ	9	17.47	₩ 70°	0.00	0.80	AVERAGE CROSS CRASS
NAME OF BURNINGSCLES IN TESTA	_		7			2,0	・1つられることには、これには、これには、これには、これには、これには、これには、これには、これ
TOTAL PARECULATES (mg)						,	THE PARTY & THE ASS.
PASE .	35	37.9	1 11	5,50	52.9	6.06	BUREE .
	dap.		14.8			24.6	- C7%
PLIER .	35.0		10		-	2	1
MINUS AVE DLANK	9,6		9.0			8	SCOTO SE ANK
TOTAL PASTICULATES (6)~	6.136	0.807	0.072	đ	¢	0.0043	TOTAL PARTIES ATES AND
TOTAL DRY WOOD USED (kg)=	Not detastained	72.5	P.C. 8			70.0	TOTAL DRY WOOD HEED AND
BURN RATE (DRYNGA)=	117	94	1,02			3,6	BURN RATE (DRY Korth?)=
AIRFEEL PATIO	£	58	552	25B		123	Alkatuel Bano-
PARTICULATE EMISTICAR							PARTICULATE EMISSIONS:
Dike.	502		Š	272		2,42	₩ Dycom
atility.	<b>₹</b> 22		126.5		_	\$2.7	and a second
AVE. DALLY glara	7	<u>5</u>	17.6	4	92	7	ANE, DAILY ghre
1030	1124	1.60.2	A. 50%	\$27.0	A CR		1000
9260	450		des			Q.	1 11 11 11 11 11 11 11 11 11 11 11 11 1
AND DAILY office	28.6		6.00		-	2	11 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
ADDITIONAL FIENS:						ì	Approvat IFFAS
AVE, BURN CYCLE LENGTH (N) >	4,02	7 32	3,52	2.48	27.2	173	AVE. BURN CYCLE LENGTH RATE
WET No USED/ BURN OYCLES	Not defermined	123	10.5			18,3	WET KO USED / BURN CYCLES
# WOOD LOADS/BURN CYCLE=	Not definitioned		64	7	s,	39.1	# WOOD LOADS/BURN CYCLE.
AVE WOOD LONG (MET hg)~	Not defermined		5.5			£.	AVE WOOD LOAD (WET ke)=
AVE. WOOD USABEDAY (MET kg+	Not defermined	12.4	[67	15,7	67.3	35.5	AVE. WOOD USAGEDAY INSTITUTE
AVE. AMBIENT TEMP (DESTREES C)	Wat delegamined	4.	£.	_	••	18.6	AME AMBIENT TEMP (CRESHEES CH

@ 0087008

92-118.06

				ſ	1						
		ROSINS			MOSSTL	MOISTURE AWALYSS	Yss	MASO	MASONRY HEATERS	SED File	
					(connection)	(CONTRACTIONAL, FPEELACE)	(SON)				
NOUSE AND ILINE	A08	888	27.2								
SAMPLE DATES:	27727	213-	3		7 E	6	2 5	Š	52503		
	i element	4/24/01	1 DHAY		1200	27.7.06	1000	in the second			
MELLACE LINE	300	NG CI	NEGR	<u>X</u>		ŝ	9	GALINDORSA	- Section	N. C. C.	
Coc year.		25. BOST	C.	AVERAGE	MENTER BY	VENTUNA	VENTORIA	HEATER	30.0	ALCO LE	
FEET MONETHER		A 1	. FR		0.718	<u> </u>	0,51R	E V	6.8		
	Š	ISIOW TO			TEIGH # \$1	SOM MOSS	PR ADOR	TOTAL NOTE	TZION PO		
	L						1				
CONTRACTOR SOME SANDONE	8	•	8	41.5		1	25.55	10.17		5	
AND STATE OF	i i	Į.	ò		;;	16.78	Ą	27.22	9	ŀ	TANK A DESTRUCTION OF THE PROPERTY OF THE PROP
The contract of the contract o	1		\$		*	¥	Ø	¥	Ě	Ē	TO MANAGE TO SERVICE OF THE PROPERTY OF THE PR
AND CATION ACCOUNTS DECIDE	e e	•	a R	•	20.05	\$5.44 4.44	Ŕ	17.74	2 5	į	A CONTRACTOR OF THE PARTY OF TH
NOTAL TACKED STORY CONTRACT	R		R	2	20.5	8	2	10,1	14.	2	AND CHARGE AND COUNTY OF THE PARTY OF THE PA
	9		ž	_	r.	202	8	477	404	•	
THE POST OF THE PARTY AND THE	į	00		_	代が	Q.	ž	202	G		
CONCRETE SALES SAL	ă '	•	ž	2	EP.	ğ	Cast?	246	100	•	ACA STANDARD MAND MAND (ACT EMERS SOLD
AVERTICAL TOPS OF THE PROPERTY.	7 j		~		*	~	ñ	n	2	î	
ACTION TO SELECT	2	•	è	_	900	0000	0.00	0.100	010	200	
Market Service of Service Control of Service Contro	8	4	0.0	7.4	90	-0	25	2.60		1	
MANAGE STATE CONTRACTOR OF THE STATE OF THE	_	•	æ	8	~	<b>.</b>	-	ş	*	1	
Date of the state			_				-	•	-	3	
	9		ž		B	27.0	78.7	283	7	\$	CONTRACTOR OF THE PARTY OF THE
	F .		70,		7	16.7	9	9		1	
	2	200	ă		3	8	475	9 2	3	į	
POUR GARDINA NAME :	2		e c		3	ą	ąc		ŕ		•
The state of the s		4	9.50	0.0965	: T	0.107	0130	¥00	1		
STREET, STREET	7	ri .	9,53	u	H	£5.	Ś	127	1	Į.	TOTAL THE PERSON SECTION
The state of the s	ğ	200	Ŧ	a	201	2	256	4.00	3		
PARTICIONAL TRIBUTARS	è	Ē	9	ğ	\$	2	Ď	8	Я		AND FUEL MATCH.
- Carlo		4	,				-		_		PARTICULAR FAISCOUR
		200	2	3	ij	ń	ų T	*	S,	2	
AND DATE YOUR			2		<b>3</b>	9.4	19.4	3	5:3	10	
CO PUISSIONE	3	Ŋ		84	Q.	ī	701	3.	ॱऱ्	2	
6,50	2	2	-,	-							CO EMISSONE:
	į	ą		3.	1087	201)	1001	20.0	2	g	1000
AME, DAILY PRINCE			ē,	<b>3</b>	ř.	Ã	Ŕ	ង	ž	8	Charles .
ADDITIONAL TISKS:	į	Ē	1	3	7.	\$3.5	406	G	6	P	AVE DALY SOLD
AVE BURKCYCLE! EXSTA (b).		3	,	i	;		•				ADDRENAL TTENES
WETTon USEDV BUTTAL CYCL EX	į	į	1	2 5	9 1	Ŗ.	200	<b>♀</b>	ž	OCT.	AVE BURN CYCLE LEXISTY AND
* WOOD LOADSHIP COOP *		1		ħ.	6	15.1	12	23.7	23.4	N.	WET he USELY BURN CYCLE.
The State Of Colors and Colors an	? :	9 !	7.7		9	7	1	<u>.</u>	q	ij	
TOTAL STREET,		•	n		r.	2.7	r'i	41.7	ĸ	7	
ANT ANDREAT TRUE AND COURSE CH	2 %	21	2	22	6	ij	ğ	4.14	K.	R	
			5		-	5	1	•	1	•	

This 2. Surmary of Rosin, masonry beater and maisture analysis data.

9

# A REPORT ON THE PARTICULATE EMISSIONS PERFORMANCE OF MASONRY HEATERS February 13, 2008





Figure 2. Comparison of PM grams per hour for woodstoves, fireplaces, and masonry heaters.

Pigure 3. Comparison of PM grams per kilogram for woodstoves, fireplaces, and masonry heaters.



Masonry heater values normalized to a 1.0 kg/hr burn tale, the Phase II woodslove field evertes.

Figure 4. Comparison of PM average daily grams per hour for woodstoves, fireplaces, and masonry heaters.

#### A REPORT ON THE PARTICULATE EMISSIONS PERFORMANCE OF MASONRY February 13, 2008 HEATERS

Attachment 5: ASTM E1602-03



Designation: E 1602 - 03

An American Network Stondard

#### Standard Guide for Construction of Solid Fuel Burning Masonry Heaters<sup>1</sup>

This standard is turned under the fixed designation E 1602, the cumber immediately following the designation indicates the year of original adoption or, in the case of revision, the year of his revision. A number in parentheses indicate the year of last responsed A importantly equival, (4) indicates an editorial change since the last revision of responsed.

#### 1. Scope

1.1 This guide covers the design and construction of solid fuel burning masonry heaters. It provides dimensions for site constructed mesonry heater components and clearances that have been derived by experience and found to be consistent with the safe installation of those masoury heaters.

1.2 Values given in SI units are to be regarded as standard. Inch/pound units may be rounded (see IEEE/ASTM SI-10). All dimensions are nominal unless specifically stated otherwise. All clearances listed in this guide are actual dimensions.

- 1.3 This guide applies to the design and construction of masonry heaters built on site with the components and maierials specified herein. It does not apply to the construction! installation requirements for component systems that have been safety tested and listed. The requirements for listed masonry heater systems are specified in the manufacturer's instaliation instructions.
- 1.4 The design and construction of solid fuel huming masoury heaters shall comply with applicable building codes.

#### 2. Referenced Documents

- 2.1 ASTM Standards: 2
- C II Terminology Relating to Gypsum and Related Building Materials and Systems
- C 43 Terminology of Structural Clay Products
- C 71 Terminology Relating to Refractories
- C 270 Specification for Mortar for Unit Masonry
- C 401 Classification of Alumina and Alumina-Silicate Castable Refractories
- E 136 Test Method for Behavior of Materials in a Vertical Tube Furnace at 750°C
- IEEE/ASTM SI-10 Standard for Use of the International System of Units (SI): The Modern Metric System
- 2.2 UL Standards:

UL 103 Chimneys, Factory Built Resideratal Type and Building Heating Appliances3

#### 3. Terminology

- 3.1 Terms used in this guide are as defined in Terminology C 11, Definitions C 43, Terminology C 71, and Classification C 401.
  - 3.2 Definitions of Terms Specific to This Standard:
- 3.2.1 approved-acceptable to the authority having jurisdic-
- 3.2.2 authority having jurisdiction—the organization, office, individual, or agent thereof, who is responsible for approving construction, materials, equipment, installation, procedure, and so forth. In most cases in which a building permit is required, the authority is typically the building official or his agent. Where a building permit is not required, the authority is typically the owner or his agent.
- 3.2.3 bypass damper-a valve or plate that provides a direct path to the chimney flue for the flue gases or portion thereof.
- 3.2.4 capping slab-a horizontal refractory barrier covering the top of the masoury heater.
- 32.5 cleanout opening-an access opening in a flue passageway of the masonry heater or chimney that is designed to allow access to the fine for purposes of inspecting for and removal of ash, soot, and other extraneous matter that may become trapped.
- 3.2.6 damper-an adjustable valve or plate for controlling
- dust or the flow of gases, including air
  3.2.7 firebox (firechamber)—that portion of the masonry heater that is designed for containing and burning the fuel charge.
- 3.2.8 gas slot-a small fixed opening that provides a bypass for unburned flue gases, and is a critical safety feature in certain masonry heater designs (namely those of the Grundofen type with vertical flue mas) (see Fig. 1, Fig. 2, Fig. 3, and Fig.
- 3.2.9 hearth extension—the noncombustible surfacing applied to the floor area extending in front of and beyond each side of the fael loading door of the masonry heater; also applies


Sportshift & ASTM International, 100 Eart Harpot Drive, PO Box 0700, West Canadohodoun, PA 19428-2555, United States


This guids is under the purisdiction of ASIM Committee 206 to Performance of Buildings and is the direct responsibility of Subarrametee Bladid on Solid Fuel Burning Applications.

Custom edition approved Oct. 1, 2003. Published Herember 2003. Originally published as E 1601 - 94. Last previous edition E 1602 - 94.

"Pet referenced ACIM education, visit the ABIM medicita, wive estimate, or contest ACIM Customs Bervious at service@estim.org, for Annual Book of ACIM. Standards wohme information, refer to the standard's Document Summery page on the ASTM website

<sup>&</sup>lt;sup>3</sup> Available from Underwriter's Labormanes, 335 Pfingston Road, Morthbrook,





### € 1602 - 03

Fig. 3 Combination Vertical and Horizontal Channel Masonry Heater (German)

1. Capping Slab
2. Clean-Out
3. Combustion Air
4. Downdraft Channel
5. Exhaust Gas Outlet
6. Expansion Joint
7. Exterior Wal
8. Firebox
9. Fuel-Loading Door
10. Gas Slot
11. Hearth Extension
12. Heater Base
13. Horizontal Channel
14. Updraft Channel
14. Updraft Channel

to the floor beneath a masonry heater or beneath an elevated overhanging masonry heater heath.


3.2.10 masonry heater base—that portion of the support for the masonry heater, between the masonry heater and the foundation, that is below the firebox or the heat exchange

3.2.11 heat-exchange flue channel—a chamber or passageway between the freebox and the chimney flue in which heat resulting directly from combustion of fuel is transferred to the surrounding masoncy.

3.2.12 knchel—a European term used to describe a masonry heater tile; a refractory occarnic tile intended for the outer walk of a masonry heater that is designed specifically to store and transfer heat

3.2.13 Ested—equipment or materials included in a list published by an organization concerned with product evaluation acceptable to the authority having jurisdiction to conduct periodic inspection of production of listed equipment or materials and whole listing states either that the equipment or materials meet appropriate standards or have been tested and found suitable for use in a specified manner.

3.2.14 masonry heater—a vented heating system of predominantly masonry construction having a mass of at least 800 kg (1760 lbs), excluding the chimney and masonry heater base. In particular, a masonry heater is designed specifically to capture and store a substantial portion of the heat energy from a solid fuel fire in the mass of the masonry heater through internal heat exchange fine channels, enable a charge of solid fuel mixed with an adequate amount of air to burn rapidly and more completely at high temperatures in order to reduce emission of unburned hydrocarbons, and be constructed outficient mass and surface area such that under normal operating conditions, the external surface temperature of the



More—Character form combustible wells or framing may be reduced with secoginessed proteotion system, other than in front of fuel-leading documents.

FIG. 4 Clearances to Combustibles

(1) this man (4 in.) to communities training from measure, reaser (2) 200 mm (8 in.) to calling.

(3) 200 mm (8 in.) minimum extent of side wall hast strictly above. frence door.

(4) 500 mm (12 m) health extension (tipes)
(5) 500 mm (20 m) health extension (tipes)
(5) 500 mm (20 m) health extension (tipus)
(9) 1200 mm (48 so,) in from of fixel-existing doors to combusible rammod.
(7) extent of mandatory heat chiefly in from of macony hearer, resulted contribution within deer more to combusible material from flust local fing door (69) - (69) see local from 1200 mm (48 m).

(6) 190 mm (4 m) informum deerance from tide was 14 missionry hearer to heat strakel (8 mission of combusible framers).

(9) distance from flust-locating operations the was of materialy beside.
(7) + (8) + (9) The same of these must be gleater than or equal to 1200 mm (45 m.).

1200 mm (46 kn )


masonry heater (except in the region immediately surrounding the fael loading door(s)), does not exceed 110°C (230°F).

3.2.15 mortan masonry-a mixture of comentitious materials (consisting of Portland or blended cement and hydrated lime, masonry cement, masonry centent and Portland cement, or masonay cement and blended cement), fire aggregate, and sufficient water to produce a workable consistency (see Specification C 270).

3.2.16 mortar, fire clay-montar consisting of fine aggregate and fire clay as a binding agent.

3.2.17 mortar, soapstone refractory-a mixture of powdered scapstone and sodium silicate.

32.18 noncombustible nuterial--a material that, in the form in which it is used and under the conditions anticipated, does not ignite, burn, support combustion, or release flammable vapors when subjected to fire or freat. Materials reported




as passing the requirements of Test Method E 136 are, for the purpose of this guide, considered noncombustible.

3.2.19 sometone—a variety of natural stone (hydrated silica of magnesium) that is suitable for high-temperature applications in masomy heaters,

3.2.20 wing wall—a noncombastible lateral projection from the exterior wall of a masonry heater for use in bridging the space between a masoury heater and a combustible partition





#### 4. Significance and Use

- 4.1 This guide can be used by code officials, architects, and other interested parties to evaluate the design and construction of masonry heaters. It is not restricted to a specific method of construction, nor does it provide all specific details of construction of a masonry heater. This guide does provide the principles to be followed for the safe construction of masonry tierlers
- 4.2 This guide is not intended as a complete set of directions for construction of masoury heaters.
- 4.3 Construction of masonry heaters is complex, and in order to ensure their safety and performance, construction shall

be done by or under the supervision of a skilled and experienced masonry heater builder. $^4$ 

- 5.1 Foundation—Masonry heater foundations and foundation walls shall meet local building codes for standard masonry fireplaces and shall be designed with consideration given to the mass and size of the masonry heater.
- 5.2 Clearance from Combustibles-Clearances shall be in conformance with this section, as illustrated in Fig. 4.

<sup>\*</sup>The Massiery Heater Accession of North America, 1257 Stock Farm Read, Pandelph, VT 63560, with size http://www.mia-net.org, is one organization that opposite a body of knowledge on massiery hunter constraints and qualified building.

The Massiery Products Causen of fire Heath Products Association, 1464 M. Kent Street, Suite 1001, Arlangton, VA. 22209, web may high/inventerstraints occupy, is nother organization that represents both manufacturers and qualified building of

muscusy heaters

- 5.2.1 Clearance from Foundation—All combustible structural framing members shall have a clearance of not less than 50 mm (2 in.) from the masoury heater foundation.
- 5.2.2 Clearance from Fuel-Loading Door—Maintain a minimum clearance of 1200 nm (48 in.) from combustible materials to fuel-loading doors, unless an engineered protection system as specified in 5.2.2.1 is provided, except for clearance directly in front of fuel-loading doors. A minimum clearance of 1200 mm (48 in.) shall be maintained in front of fuel-loading doors. This dimension shall not be reduced for any reason.
- 5.2.2.1 Clearance from fuel-loading doors to combustible materials may be reduced, ofter than in front of fuel-loading doors, if the combustible material is notected by an engineered protection system acceptable to the authority having jurisdiction. Engineered systems installed for the protection of combustible material shall limit the temperature of the combustible material to 50°C (90°P) above ambient temperature. Systems shall be designed upon applicable heat transfer principles, taking into account the geometry of the system, the heat loss characteristics of the structure behind the combustible material, and possible abnormal operating conditions of the maserny better.
- 5.2.2.1.1 When an engineered protection system is used to reduce the perpendicular clearance from fuel-loading doors, it must extend a minimum of 200 mm (8 in.) above the fuel-loading doors or firebox opening. In addition, the sum of the dimensions from the fuel-loading doors, the distance from the heater to combustible material, and the length of the protection system in front of the heater face shall be no less than 1200 mm (48 in.).
- 5.2.3 Clearance from Rear, Side, and Front Walis— Clearance from a masomy heater to combustible situating freming and other combustible materials shall be not less than 100 mm (4 in.), unless an engineered protection system is provided, or a protection system accepted by the authority having jurisdiction is provided.
- 52.3.1 Clearance from a masonry heater to combustible materials may be reduced by the use of materials or products listed for protection purposes. Materials and products listed for the purpose of reducing clearance to combustibles shall be installed in accordance with the conditions of the listing and the manufacturer's instructions and shall meet the criteria of Section 5.2.2.1.
- 5.2.4 Clearance from the Ceiling—The clearance from the masonry hoster capping slab to the ceiling shall be a minimum of 200 mm (8 in.).
- 5.2.4.1 Extensions of Exterior Withes to Coiling—When exterior masomy wythes of the masomy heater are caused to the ceiling, invalate and vent the top of the masomy heater above the heat exchange channels to tedore possible static heat buildup.
- 5.2.5 Wing Walls—Wing walls may be added to a mascray heater and used as room partitions. Wing walls located at the corners of a masonry heater for the purpose of forming a room divider shall be a minimum of 100 mm (4 in.) in length and a maximum of 100 mm (4 in.) in thickness and be constructed with noncombustible materials. Wing walls located more than

- 200 mm (8 in.) from a corner of the masonry heater shall be a minimum of 200 mm (8 in.) in length and a maximum of 100 mm (4 in.) in thickness and be constructed with noncombustible materials.
- 5.3 Finstox Floor....The firebox floor shall be a minimum thickness of 100 mm (4 in.) of noncombustible material and at least the top 50 mm (2 in.) shall be refractory material. The firebox floor or a portion thereof may also contain a cast iron grating.
  - 5.4 Hearth Extension:
- 5.4.1 Masonry heaters shall have hearth extensions of brick, concrete, stone, tile, or offer approved noncombustible material properly supported. Remove wooden forms used during the construction of hearth and hearth extension once construction is completed.
- 5.4.2 Closed Door Fireboxes—With a masonry heater designed to be fitted with a closed door of glass or metal, the hearth extension shall be at least 500 mm (20 is.) in front of the facing materials and at least 300 mm (12 in.) beyond each side of the masonry heater opening. When a raised hearth of at least 200 mm (8 in.) in height is used and the hearth extension is located at the base of the door, the hearth extension can be reduced to 400 mm (16 in.) in front of the facing materials.
  - 5.4.3 Open Fireboxes:
- 5.4.3.1 Where the firebox opening is less than 0.6 m<sup>2</sup> (6 ft<sup>2</sup>), the hearth extension shall extend at least 400 mm (16 in.) in front of the facing materials and at least 200 mm (8 in.) beyond each side of the firebox opening.
- 5.4.3.2 Where the fluebox opening is  $0.6 \, \mathrm{m}^2$  (6  $\mathrm{ft}^2$ ) or larger, the beauth extension shall extend at least 500 mm (20 in.) in front of the facing materials and at least 300 mm (12 in.) beyond each side of the firebox opening.
- 5.4.4 Where a firebox opening overhange a floor, the hearth extension shall also cover the area beneath the overhang and extend beyond the firebox opening as specified in 5.4.2.
- 5.5 Cleanout Openings:
- 5.5.1 Chimney flues shall have a cleanous access at their base.
- 5.5.2 Heat Exchange Channels—If the design limits natural access, install cleanout openings or a means for cleaning all chimney flues and heat exchange areas. If an ash dump or grate is provided in the firebox, provide a right-fitting cover of noncombustible material, 3 mm (% in.) minimum thickness, at the base of the ash pit. Cleanout doors for the foundation shall have a minimum size of 200 by 200 mm (8 by 8 in.). Shall the opening to facilitate inspection, cleaning, and maintenance of the masoury heater.
- 5.6 Outside Combustion Air—When required by the local building code, provide a dust with a minimum cross-sectional area of 7700 mm. (12 in.) or equivalent. When outside combustion air is required by the authority having jurisdiction the dust shall have a damper that oan be fully closed when not in use. Materials shall be non-combustible and methods of construction shall comply with the requirements of the authority having jurisdiction.
- 5.6.1 In applications in which outside air is introduced directly into the farebox, the air duct must enter the building at a level below its firebox.

ģ

- 5.6.2 Design and position the air inlet to prevent live coals from entering the air duct. To prevent rodents from entering the air duct, cover the outside entry opening of the duct with a 6 mm (14 in.) corrosion resistant wire mesh.
- 5.6.3 Ash Pit Located in Poundation.—When outside air is introduced into the firehex via the ash pit, introduce the air duot through the upper region of the ash pit wall.
- 5.6.4 When outside air is introduced into the firebox, construct the air duct from noncombustible materials.
- 5.7 Heat exchange channels:
- 5.7.1 Heat exchange channels shall be built with frebrick, soupstone, or other refractory materials laid in refractory mortar, fire clay mortar, or soupstone refractory mortar. Masonry units shall be laid with full mortar joints.
- 5.7.2 Capping Slab—A capping slab shall be of at least 57 mm (2¼ in.) in actual thickness above the uppermost heat exchange channels.
- 5.7.3 Gas Slot—When required, a gas slot shall have a cross-scotloral area of at less the of the firebox floor area and a height of 30 mm (1¼ in.) Refer to Fig. 1, Fig. 2, Fig. 3, and Fig. 6 for typical locations.
- 5.8 Shut-off Damper(s)—One or more shut-off dampers may be installed near the juncture of the masonry heater and chimney or in the chimney. Each damper shall have external controls and be constructed of cast non or steel of at least 12 gauge, 2.5 mm (0.10 in.) in thickness. To reduce the possibilities of toxic gases escaping into the room, the cross-sectional area of the damper's opening shall be not less than 5% of the interior cross sectional area of the flue.

- 5.9 Chinney—Vent masorcy heaters with a tow-heat type masorry chinney approved by the authority having jurisdiction or with a factory-built residential type chinney that meets the requirements of UL 103 Hz.
- 5.9.1 The chimney shall not be supported by the interior walls of the masonry heater unless specifically designed to do so. The chimney can be built integrally with an exterior wythe of the masonry heater, provided the exterior wythe is constructed of solid masonry and has a minimum thickness of 100 mm (4 in.).
- 5.9.2 Plus sizes shall be in accordance with the design specification of the builder or the designer of the masomy beater.
- 5.10 Chimney Connector.—The chimney connector shall be accessible for inspection and cleaning. Chimney connectors shall be aintight and fitted with autight joints. Where differential movement can take place between a masonry heater and chimney, make provision for this movement in such a way are maintain the integrity of the connector joints. Materials and methods of construction shall comply with the requirements of the authority having jurisdiction.

#### 6. Typical Masoury Heater Types

6.1 There are several different masonry heater types. Fig. 1, Fig. 2, Fig. 3, Fig. 5, and Fig. 6 show the names and schematic sections of typical masonry heater designs.

#### 7. Keywords

7.1 brick; Contraflow; firebrick; fire clay mortar; Cruandofen; Kachelofen; Kakeloga; masonry heater; mortar; refractory mortar; Russian; scapptone refractory mortar

ASTM literaphone lakes no position respecting the validity of any potent rights asserted to contention with any faint members in this standard. Users of the standard are expressely anneas that determination of the validity of any such potent rights, and the max is intergement of such digits, are entirely their outer responsibility.

The slandard is subject to receive all any time by the responsible factories committee and must be revisived every true years and short terrespond this decrease of the deditions elements are swifted when the responsible for the deditions elements and should be addressed to 45 M interneural Headquelies. You community was received consideration of a modify; of the responsible technical committee, which you may allow it, you feel that your comments have not responsible take the responsibilities and the same parties of the codess whom to the ASTM Committee on Standards, of the codess whom takes.

This identism is copyrighted by ASTM International, 100 Bert Harbor Chris. PO Box CTOD, West Construction, PA 19426-2858, United States. Internation in participation of the state state of the participation of the participation of the state of the participation of the participation

ş

# A REPORT ON THE PARTICULATE EMISSIONS PERFORMANCE OF MASONRY HEATERS February 13, 2008

Attachment 6: Summary of Emission Test Reports for Masonry Heaters

	_	1	7					Г			7		7		1	- 1		Т	}	7		<u> </u>		7		<del></del>		<del></del> -
Average FM Engissions (gluona)	0.8 - 1.1 1.3 - 2.8		8 9. 9.	1.8	1.5	0.3	23.3	4.	5.6		1.26 (Daily)			0.42 (Daily)	3.4		5.5	4.7		R.Z.	3.0	3.8						:
Average PM Emissions (g/kg)	:	4.4	9. Se Se Se	1.9	4.6	4.	5.7 5.8	1,4	5.6		2.96			67	3.9		28	1.70		2.8	2.5	1.6		2.6	3.5	0.	2.7 (2.0 using ESS)	3.3 (2.0 using ESS)
Average Burn Average FM Rate (kg/hom) Emissions (g/kg) (While	( <b>*</b> m.m.q		80 VI						\$.		1.78			7.7								1.9		10.4			4.0	F.E.
PM Endenious Rouge (2/kg)	0.2 - 1.6						•														·						24 - 2.9	2.3 - 5.0
Bunge (kgillom) Runge (glig)																											3.8 - 4.1	3.0 - 3.3
	Grandofen Contraffore	Average	Coerrellow Russian (See Note 2)	Biotec	Grundofin Hem. Kit	Royal Crown	Tudikini Avertese	Grundoßen	Сопилово																		Swedish Style	Swadish Style
fineling Protocol	VPI Proposed Protocol		Eemsowner operated	Jac.	operated			Homeowner			Боласумаст	operated		Homeowner	Ношеомпи	nomendo	Celorado	er to	washington state		Washington State	Colorado	•	Colorado	Colorado	Colorado	Colorado	Colorado
Sampling Method Broking Protocol Renter Libertification	Based on method 5G			AWES				AWES			AWES			AWES	AWES		ESS		224		ESS Washington State	ESS Washington	Inste	AWES	AWES	AWES	proposed ASTM (Now ASTM E2515) & ESS	proposed ASTM (Now ASTM E2515) & ESS
Wood Type	Douglas far 4xe s	П			- 6	Auder		Douglas far	cordwood			cordwood		1993 Douglas fir	Mople and		Oak and Cherry	Cordwood	Doughs hr	•••	Douglas fir dinemional oribe (3 cribs)	Douglas fir	dimensional crib (1 crib)	1999 Cordwood	1999 Cordwood	1999 Cordwood	Douglas fir cordwood	2006 Douglas Er F dimensional cribs
Date of Test Roport	1990		1991	1991-1992 Douglas fir				1992			1992				1994		1996	2000		9661	1997	1997		<u></u>			300%	
Report Name	Masoncy Ecoter Emissions Tost Mathod	Development (VPI)	In-Home Evaluation of Sensitions from Maroury Fireplaces and Heaters (OMM)	Summary Report of In-	Home Emissions and	efficiency Performance of Five Commercially	Available Masonry	Description of Emissions	from Masonry Honture	Freplaces in Homes (OMAN)	for Element Terrahamble of	Enistions from a Tomp	Cast 2001 Mesonry Hester	Macterrial Swedish	MobergRoyal Crown	MRC-3036 (OMIND)	Moberg 3042 (Chant)	1	Mobers 3042 (OMME)	U.S.E.P.A. A.P-42	Report on Finnish-atyle masonry heater KTV2100 (OMMN)	Test 1 Report on Finnish-style	matenty heater KTU2100 (OMM)	Report on Finnish-style, masoury heater TU1000 (OMM)	Report on Finaish-style masomy bester TUZ200 (OMNI)	Report on Famish-style masonry heater TUZ450 (OMMI)	Test Report on Swedich eyte masoury heater built by Jerry	Tost Report on Swedish style mastenry heater built by Jerry Frisch (OMMI)
M	Reference		<u>н</u> я с в	S		υ υ				A.		<u>4 144 </u>		is in		<del>შ</del> —	1	l	딡	ĭ			Ę	и	ы	Ed	Ę,	77.

Attachment 7: Reference Reports

- A. Stern, C. H, Jaasma, D. R. and J. W. Shelton, <u>Masonry Heater Emissions Test</u>
  <u>Method Development</u>, Wood Heating Alliance, March 1990.
- B. Barnett, S. G., <u>In-Home Evaluation of Emissions from Masonry Fireplaces and Heaters</u>, Western Clay Products Association, Prepared by: OMNI Environmental Services, Beaverton, OR, Report # 80-10201, September 6, 1991
- C. Barnett, S. G., <u>Summary Report of the In-Home Emissions and Efficiency Performance of Five Commercially Available Masonry Heaters</u>, Masonry Heater Association, Prepared by: OMNI Environmental Services, Beaverton, OR, Report # 80-13301, May 22, 1992 (Revised June 1, 1993).
- D. Barnett, S. G., McCrillis, R. C. and R. B. Crooks, <u>Evaluation of Emissions from Masonry Heaters and Masonry Fireplaces</u>, OMNI Environmental Services, U. S. Environmental Protection Agency, Mutual Materials Company, Report # 92-118.06, 1992
- E. Bighouse, R, and S. G. Barnett, <u>In-Home Evaluation of Emissions from a Temp-Cast 2001 Masonry Heater</u>, Temp-Cast 2000 Masonry Heater Manufacturing, Inc., Prepared by: OMNI Environmental Services, Beaverton, OR, Report No. 80131-01, May 8, 1992
- F. In-Home Evaluation of Emissions from a Mastercraft Swedish Heater Kit Masonry Heater, Mastercraft Masonry, Brush Prairie, WA, Prepared By: Science Applications International Corporation, Beaverton, OR, March 23, 1993.
- G. Evaluation of Efficiency and Emissions from a Moberg/Royal Crown MRC-3036

  Masonry Heater, FireSpaces, Inc., Portland, OR, Prepared by: OMNI Environmental Services, Beaverton, OR, Report No. 001S-013B, May 28, 1994.
- H1: Moberg 3042 Masonry Heater Emissions Testing Report (Compliance with Colorado Regulation No. 4), FireSpaces, Inc., Portland, OR, Prepared by: OMNI Environmental Services, Beaverton, OR, Report No. 001-S-02-3-B, January 1996.
   H2: Moberg 3042 Masonry Heater Emissions Testing Report (Compliance with Washington State UBC Section 31-2), FireSpaces, Inc., Portland, OR, Prepared by: OMNI Environmental Services, Beaverton, OR, Report No. 001-S-02-3-A, January 1996.
- I. Report on Revisions to 5<sup>TH</sup> Edition AP-42 Section 1.10 Residential Wood Stoves, Contract No. 68-D2-0160, U. S. Environmental Protection Agency, Research Triangle Park, NC, July 29, 1996.
- J. J1: Test Report: Masonry Heater Particulate Emissions and Overall Efficiency. <u>Tulikivi Oy Model KTU-2100</u>, Tulikivi Oy, Juuka, Finland, Prepared by: OMNI-Test Laboratories, Inc., Beaverton, OR, Project # 020-S-01-03, May 1997.

- J2: Test Report: Masonry Heater Particulate Emissions and Overall Efficiency.

  <u>Tulikivi Oy Model KTU-2100</u>, Tulikivi Oy, Juuka, Finland, Prepared by: OMNITest Laboratories, Inc., Beaverton, OR, Project # 020-S-01-03, May 1997.
- K. <u>Tulikivi Oy; Model TU 1000 Emission Testing Report (Protocol Conformance with Colorado Regulation No. 4)</u>, Tulikivi Oy, Juuka, Finland Prepared by: OMNI Environmental Services, Beaverton, OR, Report No. 020-S-06-3, April 29, 1999.
- L. <u>Tulikivi Oy; Model TU 2200 Emission Testing Report (Protocol Conformance with Colorado Regulation No. 4)</u>, Tulikivi Oy, Juuka, Finland Prepared by: OMNI Environmental Services, Beaverton, OR, Report No. 020-S-06-3, April 29, 1999.
- M. Tulikivi Oy; Model TU 2450 Emission Testing Report (Protocol Conformance with Colorado Regulation No. 4), Tulikivi Oy, Juuka, Finland Prepared by: OMNI Environmental Services, Beaverton, OR, Report No. 020-S-06-3, April 29, 1999
- N. <u>N1: Emissions Report, Swedish Kakelugn Style Masonry Heater</u>, Built by Jerry Frisch, Prepared by: OMNI-Test Laboratories, Inc., Beaverton, OR, 2006.
  <u>N2: Emissions Report, Swedish Kakelugn Style Masonry Heater</u>, Built by Jerry Frisch, Prepared by: OMNI-Test Laboratories, Inc., Beaverton, OR, 2006.

#### Attachment 8: Reference A - Report Cover Page

7

Final Report on

MASONRY HEATER EMISSIONS TEST METHOD DEVELOPMENT

Submitted to

Wood Heating Alliance 1101 Connecticut Ave. Suite 700 Washington, D.C. 20036

and

Fireplace Emissions Research Coalition

Submitted by

Curtis H. Stern and Dennis R. Jaasma

Department of Mechanical Engineering Virginia Polytechnic Institute & State University Blacksburg, VA 24061

and

Jay W. Shelton Shelton Research, Inc. P. O. Box 5235 Santa Fe, NM 87502

March, 1990

Attachment 8: Reference A - Executive Summary

#### **EXECUTIVE SUMMARY**

A standard test method for determining carbon monoxide (CD) and particulate matter (PN) emissions from masonry heaters has been developed. The method specifies the fueling protocol and laboratory measurement procedures for determination of both emission rates (g/hr) and factors (g/kg). The fuel load size and fueling intervals are dependent upon the firebox volume of the masonry heater.

The test starts with the heater at ambient temperature and involves five firings to achieve burn rates in two ranges. The low burn rate range, used for the first two firings, is 0.70-1.10 dry kg/hr. The high burn rate range, used for the last three firings, is 2.10-3.30 dry kg/hr. Emission samples are extracted from a dilution tunnel with a set flow rate and configuration. PM sampling is similar to EPA Method 5G for wood stoves. CO concentration is measured by a nondispersive infrared (NDIR) gas analyzer. The emissions results for each firing are burn-rate weighted according to EPA Method 28 to obtain the overall emission totals for the test cycle.

The emissions were measured for a Grundofen and a Contraflow type masonry heater. The averages for the two heaters of the EPA weighted average emission rates were 67 g/hr CO and 1:4 g/hr PM. In a parallel effort, a field sampler for masonry heaters was developed and tested in the laboratory. The field sampler shows acceptable agreement with the standard test method for CO emissions, but the PM emissions results are consistently high for reasons as yet unknown.

Attachment 9: Reference B - Cover Report Page

### In-Home Evaluation of Emissions From Masonry Fireplaces and Heaters

Prepared for:

Western States Clay Products Association

3130 La Selva, Suite 302 San Mateo, California 94403

Prepared by:

Stockton G. Barnett

OMNI Environmental Services, Inc. 10950 SW Fifth Street, Suite 160 Beaverton, Oregon 97005-3400

September 6, 1991

80102-01

# A REPORT ON THE PARTICULATE EMISSIONS PERFORMANCE OF MASONRY HEATERS February 13, 2008

Attachment 9: Reference B - Executive Summary

### **Executive Summary**

While woodstoves have undergone extensive regulation for almost ten years, fireplaces have only recently begun to be regulated. Capitalizing on the woodstove regulatory experience, this project was commissioned by Western States Clay Products to be the first research project to obtain basic baseline emissions data on masonry fireplaces and masonry heaters under real-world conditions in homes. Direct comparison of results with previous field studies of woodstoves and pellet stoves can be made:

The main objective of the current project was to measure particulate and carbon monoxide emissions from a baseline of conventional fireplaces and a group of potentially cleaner-burning fireplace designs and masoury heaters. Additional objectives were to evaluate the effects of wood moisture and altitude on conventional fireplace emissions.

To ensure widespread applicability for the Pacific Northwest and tight scientific control, the Portland, Oregon area was chosen as the field area, Douglas fir was used as the fuel, and fuel moisture content was held constant at 20%. All homeowners burned as they normally did and no instructions on burning techniques were given. Five conventional fireplaces, two Rosin fireplaces, one modified Rumford design, and two masonry heaters were evaluated.

The Automated Woodstove Emissions Sampler (AWES), which has been used extensively in field studies of woodstoves and peliet stoves, was used to measure emissions. The samplers were operated for seven days in each home. Typically each home burned their fireplace once a day. Tests were conducted from December 1990 through March 1991. An additional test on one of the Rosins was conducted in June 1991.

The tests provided information on how homeowners burn their fireplaces. For the conventional fireplaces, the average burn rate was 3.45 dry kg/hr, the average burn cycle tength was 4.3 hours, the average number of wood loads per burn cycle was 4.4, and the average wood load weight was 9.4 wet pounds. Of these variables, the only one with a large amount of variation was the average wood load weight, which varied over a range of 3:1.

Masonry heater burn patterns were quite different. Average burn rate for the combustion period was 8.2 kg/hr for the Contraflow and 2.5 kg/hr for the locally built Russian unit. Average burn lengths were 2.2 and 2.3 hours, respectively, and wood loads averaged 47 and 15 wet pounds, respectively. Both heaters were burned only once or twice per day as needed to heat the homes.

Particulate emissions<sup>2</sup> from the conventional fireplaces averaged 24.9 g/kg, 82.7 g/hr, and 14.1 average daily g/hr. These values are near the upper end of the range of results in the literature, which comprises mostly laboratory tests. CO emissions from the conventional fireplaces averaged 107 g/kg, 360 g/hr, and 64.5 average daily g/hr.

<sup>1</sup> This heater was built by a local mason who had no prior experience in masonry heater design.

<sup>&</sup>lt;sup>2</sup> Particulare emissions in this report are expressed in AWES units which are directly comparable to all previous field woodstove results. Values for EPA Method 5H, the lab certification method, would be 10-20% lower.

### A REPORT ON THE PARTICULATE EMISSIONS PERFORMANCE OF MASONRY HEATERS February 13, 2008

Attachment 9: Reference B – Executive Summary (cont.)

Emissions from the Rosin fireplaces were generally less than 50% of those from the conventional fireplaces. A r-test indicated that the g/kg difference was significant at the 98% probability level. Particulate emissions averaged 10.4 g/kg, 33.2 g/hr, and 9.9 average daily g/hr. CO emissions averaged 52.5 g/kg. 158 g/hr, and 47.3 average daily g/hr.

Emissions from the Contraflow masonry heater were about half those of the locally designed and built Russian heater. Contraflow particulate emissions were 5.6 g/kg, 45.7 g/hr, and 5.6 normalized average daily g/hr. CO emissions were 41.0 g/kg, 336.8 g/hr, and 31.0 normalized average daily g/hr. Emissions from the locally designed Russian unit were about twice as high.

The format in which emissions results are presented is of great importance. For example, use of different formats can result in as much as an 8:1 difference in comparative emissions results. Grams per hour (which is used for woodstoves) is considered the poorest representation of fireplace/masonry heater emissions because these types of devices are only burned for a few hours each day. Thus, use of g/hr greatly exaggerates emissions contributions to airsheds. A new term, average daily g/hr, is introduced which appears to be more appropriate. This format portrays the total amount of pollution that a given combustion device contributes to an airshed on a daily basis. Average daily g/hr is used rather than grams per day to facilitate a direct and easy comparison with the hody of woodstove data which is expressed in grams per hour. Grams per kilogram produces somewhat similar rankings for fireplaces, but is less appropriate to meet the objective of quantifying the amount of pollution per day. It is, however, valuable in calculating the total emissions contribution per burning season for any residential biomass combustion device.

To facilitate direct comparison of masonry heater results with those of woodstoves, the term normalized average daily g/hr is used. This term refers to average daily g/hr at a burn rate of 1.0 kg/hr, the field average for certified woodstoves. This term is equal to g/kg.

The effects of wood moisture (range 15% to 24%) on emissions from a conventional fireplace were significant above 20% moisture. Emissions ranged from 22.1 at 15% moisture to 41.4 g/kg at 24% moisture. The effect of altitude on emissions could not be measured because a second variable—long burns associated with the fireplace heing burned only on weekends—was present.

The real-world data collected in this project can be used to negotiate with regulators to develop fair and equitable regulations for all stakeholders. Efforts should be made to ensure that the relatively clean-burning Rosin be acceptable for burning within any of the new regulations.

The data from this project should be used as the foundation for the development of a realistic emissions laboratory standard for masonry fireplaces and heaters<sup>3</sup> and to evaluate candidate laboratory test methods. Considering the large mass and lack of portability of masonry fireplaces and heaters, in-home testing (as conducted in this project) must be considered an acceptable certification procedure.

The Fireplace Emissions Research Coalition (FERC) laboratory test procedure of Virginia Polytechnic Institute (VPI) should be evaluated for applicability to masonry fireplaces by comparing the Brick Institute of America (BIA) results with those of the current project. The VPI masonry heater laboratory procedure

<sup>&</sup>lt;sup>3</sup> This development process would philosophically follow closely the system currently being used to develop the scress test protocol for woodstoves which will be used to evaluate potential product durability problems.

### Attachment 9: Reference B - Emission Comparison






Figure 10

#### COMPARISON OF PARTICULATES; G/KG WOODSTOVES, FREPLACES, MASONRY HEATERS



Eigure 12

# AVERAGE DAILY G/HR PARTICULATES FOR WOODSTOVES, FIREPLACES, MASONRY HEATERS



Masonry heater values normalized to a 1.0 kg/hr burn rate, the Phase II woodstove field average.

Figure 11

Attachment 10: Reference C - Report Cover Page

Summary Report of the In-Home Emissions and Efficiency Performance of Five Commercially Available Masonry Heaters

Prepared for:

The Masonry Heater Association

Prepared by:

Stockton G. Barnett
OMNI Environmental Services, Inc.
10074 SW Arctic Drive
Beaverton, Oregon 97005

May 22, 1992

(Revised June 1, 1993)

80133-01

Attachment 10: Reference C - Executive Summary

## **Executive Summary**

General ....

Emissions regulations for residential woodburning devices have become tighter in recent years. In 1986, the EPA established a woodstove certification program that went into effect in two stages in 1988 and 1990. Masonry heaters, which essentially function as high-mass, rapidly burning woodstoves with a large heat storage capacity, were exempted from this program by virtue of their large mass.

More recently, certain airsheds in the west, with extensive residential woodburning, have been declared in nonattainment by the EPA for airborne particulate matter of less than 10 microns in diameter (PM<sub>10</sub>). State Implementation Plans (SIPs) have been written to develop air pollution reduction strategies to bring these areas into compliance. Unfortunately, masonry heaters have not been included in this process because they cannot qualify for EPA emissions certification due to their large mass. Hence, they have not been placed on the EPA's Reasonably Available Control Measure (RACM) Emissions Reduction Credit list. Accordingly, state and local governments have excluded masonry heaters from their own lists of emissions reduction control strategies. Recently the EPA, in recognition of this problem, instituted an "in-home" emissions test option for "non-affected" residential wood combustion RWC devices such as masonry heaters. These tests provide more realistic emissions and efficiency information than lab tests and their results can be used to obtain emissions reduction credits.

### Objectives and Methodology

This project's main objective has been to sample a representative population of commercially available masonry heaters in homes. The data will be used by EPA to produce a masonry heater AP-42 emissions value which will be used to calculate an emissions reduction credit. An additional objective has been to explore these heaters as potentially very clean burning technologies that can qualify as low-emitting Best Available Control Measures (BACM).

Particulate (PM) and carbon monoxide (CO) emissions and not efficiency were measured on five masonry heaters in western Oregon and Washington in 1991 and 1992 using OMNI's Automated Woodstove Emissions Sampler (AWES). Each heater was operated by the homeowner in his normal fashion and was fired seven to ten times during the week-long test. In four of the five houses the heater was the only source of heat.

#### Results

PM emissions for the five heaters averaged 3.2 g/kg, 1.8 average daily g/hr, and 3.2 normalized average daily g/hr. These PM values are higher than field values from certified pellet stoves and lower than from Phase II EPA certified noncatalytic woodstoves.

OMN Environmental Services, Inc. (80133-01.001)

Emissions values are "normalized" for easy comparison to 1 dry kg/hr burn rate, the average inhome burn rate for certified noncatalytic woodstoves.

Attachment 10: Reference C - Executive Summary (Continued)

CO emissions averaged 74 g/kg, 50 average daily g/hr, and 74 normalized daily g/hr. These values are comparable to Phase II EPA certified noncatalytic woodstoves.

The average net delivered efficiency was 58%, which is midway between conventional and EPA certified Phase II woodstoves. Average heat output was 7425 BTU/hr and average daily burn rate was 0.68 dry leght.

Following EPA procedures and using the most recent field data, the average masonry heater emissions reduction credit is 81% compared to 91% for certified pellet stoves and 64% for certified noncatalytic woodstoves. Because the final version of the BACM guidance document is not yet available, masomy heaters will have to be evaluated for BACM status at a later date.

OMNI Environmental Services, Inc. (80133-01.001)

Attachment 10: Reference C - Emission Results

#### **Emissions Results**

PM emissions for the five masonry heaters averaged 3.2 g/kg and 2.4 average daily g/hr (Table 1). The average daily hunn rate was 0.69 dry kg/hr. The 95% confidence limit for each test is generally about  $\pm 20\%$  of the emissions value. The 95% confidence limit for the five heater average is  $\pm 2.8$  g/kg. Tables 1 through 7 in Appendix A contain the results from each heater's emissions test.

Table 1. Summary of emissions and efficiency results for the five masonry heaters.

	İ	₽M		co	Burn Rate	Net Efficiency
Heater Model	g/kg	Ave. Daily g/hr	.g/kg	Ave. Daily g/hr	Ave. Daily kg/hr	Ave. %
Biofire	1.9	1.8	72	69	0.95	54
Gnudofen	1.4	1.5	83	92	1.10	60
Heat-kit	5.8	4.4	41	31	0.76	54
Royal Crown	1.4	0.3	69	15	0.21	65
Tulikivi	5.7	2.3	107	44	0.41	59
Averages	3.2	2.1	74	50	0.69	. 58

Average CO emissions were 74 g/kg with an average daily g/hr of 50.

Comparatively, the average PM emissions (Figure 5) were somewhat higher than emissions from certified pellet stoves (1.7 g/kg) as tested in homes (Barnett and Robolt, 1990) and considerably lower than EPA 1990-certified Phase II noncatalytic woodstoves (AP-42 value of 7.0 g/kg). The average masonry heater emissions are 79% lower than the EPA's AP-42 emissions value of 14.9 g/kg for conventional woodstoves (Table 2).

CO emissions are comparatively not as low as PM emissions. They are comparable to Phase II certified noncatalytic woodstoves but significantly lower than conventional stoves (McCrillis and Jaasma, 1991 and Reference 15).

## Efficiency

The average net delivered efficiency of the five masonry heaters was 58%. This efficiency is about roldway between the 50-55% average for conventional woodstoves and the 65-70% average for Phase II woodstoves as measured in homes (References 1,10,14,15). The average heat output was 7248 BTU/hr.

The design of the heat transfer systems is generally not quite as effective as Phase II noncatalytic stoves (Figure 6). Improvement could be made by reducing the excess air so that stack oxygen averages about 15-16% and aiming for an average stack temperature of 300 to 350°.

OMNI Environmental Services, Inc. (80133-01.001)

Attachment 11: Reference D - Cover Page

92-118.06

## Evaluation of Emissions from Masonry Heaters and Masonry Fireplaces in Homes

Stockton G. Barnett
OMNI Environmental Services, Inc.
Beaverton, Oregon

Robert C. McCrillis
U.S. Environmental Protection Agency
Air and Energy Engineering Research Laboratory
Research Triangle Park, North Carolina

Richard B. Crooks
Mutual Materials Company
Bellevue, Washington

### Attachment 11: Reference D - Excerpt from Summary

92-118.06

PM emissions from the conventional masonry fireplaces averaged 24.9 g/kg, 82.7 g/hr, and 14.1 average daily g/hr (Table 1 and Figures 2,3,4 and 5). These values are near the upper end of the range of results in the literature, <sup>3-46</sup> which comprises mostly laboratory tests and some field tests with the fireplaces being operated by laboratory technicians. The EPA recently revised their fireplace AP-42<sup>17</sup> downward from 14.0 to 10.8 g/kg. CO emissions from the conventional masonry fireplaces averaged 10 g/kg, 36 g/hr, and 64.5 average daily g/hr (Figure 6), significantly higher than the EPA AP-42 value of 61.1 g/kg.

PM emissions from the Rosin masonry fireplaces were generally less than half of those from the conventional masonry fireplaces (Figure 2, 3, 4, and 5). A t-test indicated that the grams-per-kilogram difference was significant at the 98% probability level. Particulate emissions averaged 10.4 g/kg, 33.2 g/hr, and 9.9 average daily g/hr. CO emissions averaged 52.5 g/kg, 158 g/hr, and 47.3 average daily g/hr (Figure 6). The retrofit Rosin reduced emissions by 47% compared to its conventional predecessor.

The effects of wood moisture (range, 15 to 24%) on emissions from a conventional masonry fireplace were significant above 20% moisture. Particulate emissions ranged from 22.1 g/kg at 15% moisture to 41.4 g/kg at 24% moisture (Figure 7) and CO emissions ranged from 109 to 140 g/kg (Figure 8).

#### Masonry Heater Emissions

The underfire air Contraflow masonry heater particulate emissions were 5.6 g/kg, 45.7 g/hr, and 5.6 normalized average daily g/hr (Table 2 and Figures 2, 3, and 4). CO emissions were 41.0 g/kg, 336.8 g/hr, and 31.0 normalized average daily g/hr. Particulate emissions from the non-underfire air Grundofen were only 1.4 g/kg, 5.5 g/hr, and 1.4 normalized average daily g/hr. CO emissions were 83 g/kg, 339 g/hr, and 83 normalized average daily g/hr. The Grundofen's particulate emissions are among the lowest measured for an RWC device, about the same as the cleanest-burning pellet stoves.

Three other potentially promising masonry heater designs are currently being evaluated in the field. Improvements in masonry heater design, in particular the abandonment of underfire air, are currently being undertaken. It appears that masonry heater technology holds promise for meeting the strictest of emissions standards.

#### Field Versus Laboratory Results

It is important to compare field and laboratory results since the validity of laboratory tests hinges on their ability to faithfully reflect and predict field performance. Because laboratory certification tests for woodstoves do not correlate well with field performance. If there is additional need to closely examine such relationships for each type of RWC device. There are now comparative data for masoury fireplaces, and masonry heater data will be available soon.

A project was conducted by Virginia Polytechnic Institute<sup>16</sup> (VPI) for the Hearth Products Association (HPA) which used a newly developed laboratory test protocol for fireplaces to measure emissions from both conventional and Rosin masonry fireplaces. The conventional baseline included one fireplace, and the same Rosin models which were evaluated in the current project were tested at VPI. The results (Figures 9 and 10) show that the conventional fireplace PM emissions were only about 20% of the field average and 30% of the cleanest-burning field fireplace in the corrent study. The Rosins were about the same in the laboratory as in the field. The net result is that the relative ranking of the conventional and advanced-technology fireplaces is reversed. As a result of this problem and the gross understatement of the conventional fireplace emissions, it

Attachment 11: Reference D - Data Summary

92-118.06

	Table 2	Summe	ry of	Rosin,	metoni	y heate	r and 1	Table 2. Summary of Rosin, mesonry heater and moisture analysis data.	analys	is data	, n
		ROSINS		- · · · ·	MOIST	MOISTURE ANALYSIS (CONVENTIONAL MIGHLADS)	YSIS	MASOF	MASONRY HEATERS	EHS	
HOUSE AND RUP: RAWPAS DATES: FREETAGE TYPE: RAEL YTYPE: FLEEL MOIST UNE	FOXO1 2/22/- 3/A2501 HAGEN OP. EQUIP D. FIR 20% MOUST	FORCE STREM SERVIN ROSKIN OR. EDVIN CL. SER ZOM MORST	TEION AT	ROSIN	FOI 02 27:3- 27:59:01 COSK- VENT TOWN, D. FIR 15 % MOIST	POTOLI 2005— 2713871 CON- VEWIDSYN, D. FR.	FOIGO 250- 227/21 CON- VENTIONAL D. FIR 24% MOIST	FRED 1 1976— 12750-1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	Foso) 2/27- 3/04/01 CONTRA- FLOW D. PIR 18% MOIST	MASONRY HEATUR AVSTAGE	
TATAL STREET,	1									Ī	
A OF THE FIRE PLACE BURNED.	2 22	8,55	10.75	\$1.5 0.0	27.07	35.05 \$1.41	25.5	44.24	N. C.	S :	TOTAL STOVE BUTNING HOURS
AVE. STACK TEIMP (DECREESF1)**	ğ	100	210	â	8	a		200	\$	8	AVE STACKTEND OCCURED TO
AVEOXYGEN X(STACKS, IDDDGG, F.)	2003	<u>8</u>	~	20.18		20.44	\$78	17.74	16,72	-	
TOTAL WOOD USED AVET KON	106.5	2 2	8 2	8 5		Š		16.1	4		AVE OXYGEN'S (BAB)=
WOOD MOSTURE (DITY DASIS %)-	202	200		3	3	100	1 N	38	1		WOOD MOSTLES (DRY BASIS WA
AWES FLOW RATE (LIMIN)-	1,054	FBQ*	Ž	7	-	0,004		0.04	1.004		AWESTLOW RATE (Limin)-
LENGTH OF SAMPLING CITCLE (rob) =	2 5	8 6	#V 2	25	4	'n		9			
AVERAGE COS & ICAGIA	9	90	OC C	17.0	_	200		001.0	2 6	25.5	AVERAGE COS. (BAG)
AUMBER OF BLITTY OYCLES IN TEST-	2.0	7		8		, ~		5			
FOTAL PARTICULATES (mg)		;	7	1		•					-
**************************************	9 5	1.5		20.00	ğ ş	0.10		26.2	0.7	8	
F11.74H (mg)=	2	16.0	ล	2.5	9	3	67.0	3	2 4		7.7.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1
MINUTE AVE BLANK	2	er :		2	3.0	8		9.5			
TOTAL PARTICULATES (s)=	1900	0000	-	0.0008	11.0	0,100		2020	Ö	-	
of any mette many tentols	2 7	200	_	17.7	200	225		É	120.0	0.53	TOTAL DRY WOOD USED (val-
ARPUBLIKATION	9	Ē	3	Ž	8	3	ដ	8	9		
PARTICULATE BAISSIDNE											
500	202	9		ā j	ลั	h :			2 2		
AVE. DARLY offers	2 2			200	9 5	979	201	2.	27.13	28.0	
CO EMIGSIONS:	}	!							•		OD ENISSIONS:
- Dyd	5	8.9	•	52.5	106.7	110.2	¥0.	83.5	11,0	950	_
- CONT. 1748-C. P. C.	3 3	2.7	2 5	2 :	2	8					
ADDITIONAL ITEMS:	•	Š		2	ţ	770			-	¥	AVE UNIT DIME
AVE BUNY OYOLE LENGTH (hop-	7,28	4		27	966	2			ij		
WET to USEC BURN CYCLE-	84	Q H	•	2		2				w	٠.
# WOOD LOAD ASSESS CALLS		g r		3	87	3 2	47 5	Q . (			
AVE WOOD USAGEDAY (WET ke)*	13	17	1 1			1 2			3 8	3 8	AYE WOLLD LOAD (WE) ROM
AVP. AMBIENT TEMP (DECHREST)	0.70	567		1	1	70.1					1

-

### Attachment 11: Reference D - Emission Comparison Chart

92-118.06




Figure 2. Comparison of PM grams per hour for woodstoves, fireplaces and masonry heaters.





Figure 3. Comparison of PM grams per kilogram for woodstoves, fireplaces and masonry heaters.



Masonry heater values normalized to a 1.0 kg/hr burn rate, the Phase II woodstove field average.

Figure 4. Comparison of PM average daily grams per hour for woodstoves, fireplaces and masonry heaters.

Attachment 12: Reference E - Report Cover Page

In-Home Evaluation of Emissions from a Temp-Cast 2001 Masonry Heater

Prepared for:

Temp-Cast 2000 Masonry Heater Manufacturing, Inc.

Prepared by:

Roger Bighouse Stockton G. Barnett

OMNI Environmental Services, Inc.

10074 SW Arctic Drive Beaverton, Oregon 97005

May 8, 1992

80131-01

Attachment 12: Reference E – Excerpt from Report

Every three minutes it operated for one minute. This causes the collected gases to be more dilute than those emitted during just the combustion phase. Thus, in Table 1, the Q<sub>2</sub> values are artificially high and the CO and CO<sub>2</sub> values low. This method of gas collection does not affect the calculated CO emissions values at all, however.

## **Emissions Results**

PM emissions averaged 2.96 g/kg and 1.26 average daily g/hr. Table 1 shows the results from each emissions test. The 95% confidence limit for the g/kg value is ±0.6 g/kg. Normalizing the grams per bour emissions to a 1 kg/hr burn rate as described in Barnett (1991) yields 2.96 normalized daily g/hr. The average daily burn rate was 0.43 dry kg/hr.

Average CO emissions were 82.7 g/kg, 35.2 average daily g/hr, and 82.7 normalized average daily g/hr.

Comparatively, the PM emissions (Figure 4)\* were between the emissions of certified pellet stoves as tested in homes (Barnett and Roholt, 1990) and EPA 1990-certified Phase II noncatalytic woodstoves. The Temp-Cast 2001 emissions are about 80% lower than the EPA's AP-42 emissions value of 14.9 g/kg for conventional woodstoves.

CO emissions are comparatively not as low as PM emissions. They are comparable to Phase II certified noncatalytic woodstoves but significantly lower than conventional stoves (McCrillis and Jazsma, 1991 and Reference 11).

## **Efficiency**

The average net delivered efficiency of the Temp-Cast 2001 was 61.8%. This efficiency is in between the 65-70% average for Phase II woodstoves and 50-55% average for conventional stoves as measured in homes (References 1,6,10,11). The average heat output was 4915 BTU/hr.

The net delivered efficiency is average for masonry heaters (Table 1 and Figure 5). The design of the heat transfer system could perhaps be improved somewhat by reducing the average stack oxygen to 15-16%


The woodstove values in this figure are from the summary paper by McCrillis and leasms, 1991. The Certified pellet stove values are from Barnett and Robolt, 1990, and the estempt pellet stove values are from Barnett and Fields. 1991.

## Attachment 12: Reference E - Data Summary

[	MASONRY HEAT	ER EMISSION	S RESULT	S
	HOUSE AND RUN:	TEMP-CAST		
i	SAMPLE DATES:	4/22-29/92		
	HEATER TYPE:	TEMP-CAST 20	01	
1	FUEL TYPE:	POPLAR	V1	
L	ruck tire,	rorun		
	TOTAL STOVE BURNIS	KG HOURS=	40.05 HO	URS
	% OF TIME HEATER B	URNED=	23.84 PE	
}	AVE, STACK TEMP=		199.81 DE	
	AVE OXYGEN (STACK	j <del>zz</del>	16.68 PE	RCENT
	* AVE. OXYGEN (BAG)=			****
			199.0	
Į.	TOTAL WOOD USED, ' WOOD MOISTURE (OF	TY BAS(S %)=	26.6	***
	AWES FLOW RATE(L/	MiNi=	1.08	40000
1	LENGTH OF SAMPLE		3	48×+4
1	AVERACE CO % (BAG		0.0347	****
Ì	AVERAGE CO2 % (GA)		0.53	akees
l	VCC, PPM (BAG)=	-,	2.00	****
1	TOTAL PARTICULATES	o INCRICA		
	RINSE#	31 is 1623. St. ≠1		
1.				
1	XAD≃	9.6 **		
j	FILTER=	12.3 ***	***	
l	MINUS AVE BLANK	3.9		
	TOTAL PARTICULATES		0.055 GN	
	TOTAL DRY WOOD US	ED=	71.45 KG	
ì	*SURN RT (DRY KG/H)	ouring Burn≃	1.78 KG	
ļ	AVEDAILY SURN RT (	DRY KG/H} =	0.43 KG	/HR
L	AR TO ELE RATION		56.42	
	* PARTICULATE EMIS	SIONS:		
	*GM/KG=	2,96		
Į.	GM/KG UNCERTAINTY			
ŧ	*GM/HR=	-5,29		
	Ave. daily g/hr=	1,26		
ļ	* CO EMISSIONS:		<del></del> -	
1	GM/KG≂	82,72		
	GM/HR =	147.57		
	Ave. daily g/hr=	35.18		
- <del>-</del>	*VOC EMISSIONS:	· · · · · · · · · · · · · · · · · · ·	· · · · · · · · · · · · · · · · · · ·	
	GM/KG=	0.00		
1	GM/HR=	0.00		
	Ave. daily g/hr =	0.00		
	ADDITIONAL ITEMS:			
}	AVE WOOD LOAD (WE	TLB)=	24.65	
1	AVE. WOOD USAGE/0	AY (WET LB.) =	28.43	
l	# TIMES LOADED/DAY	in production	1.14	
	AVE. AMBIENT TEMP		70.89	
	NET EFFICIENCY:	·	·/	
	COMBUSTION ESSA.			
	COMBUSTION EFFIC. HEAT TRANS. FEELC.			
	COMBUSTION EFFIC. HEAT TRANS. EFFIC= NET EFFICIENCY=			

Table 1

Attachment 12: Reference E - Graphical Presentation



11

Attachment 13: Reference F - Report Cover Page

In-Home Evaluation of Emissions from a Mastercraft Swedish Heater Kit Masonry Heater

Prepared for:

Mastercraft Masonry

PO Box 73

Brush Prairie, WA 98606

Prepared by:

Science Applications International Corporation

10074 SW Arctic Drive Beaverton, Oregon 97005

March 23, 1993

Attachment 13: Reference F - Executive Summary

# **Executive Summary**

Particulate (PM), carbon monoxide (CO), and volatile organic compounds (VOC) emissions were measured using SAIC's Automated Woodstove Emissions Sampler (AWES) systems on a first-year Mastercraft Swedish Heater Kit masonry heater located near Battle Ground, Washington in March 1993. The heater was operated by the homeowner in his normal fashion using douglas fir cordwood with 13.5% average moisture (dry basis). The unit was fired seven times during the week-long test. The AWES was operated for the entire test and its results are reported herein.

PM emissions averaged 1.90 g/kg, 1.32 average daily g/hr, and 1.90 normalized average daily g/hr. These PM values are between those obtained from certified pellet stoves and EPA certified Phase II woodstoves in the field.

CO emissions averaged 95.7 g/kg, 66.3 average daily g/hr, and 95.7 normalized daily g/hr. These values are comparable to Phase II EPA certified noncatalytic woodstoves.

VOC emissions averaged 9.57 g/kg, 6.63 average daily g/hr, and 9.57 normalized daily g/hr.

The average net delivered efficiency was 62.5%, which is in between EPA certified Phase II woodstoves and conventional stoves. Average heat output was 8105 BTU/hr and daily burn rate averaged 0.69 dry kg/hr.


## Attachment 13: Reference F – Data Summary

Table 1. Masonry Heater Emissions Results: Mastercraft Swedish

	Heater Kit.			
	SAMPLE DATES: HEATER TYPE: FUEL TYPE:	3/12/99 - 9/1 MasterCraft - Douglas Fir		Heater Kit
	Total Burning Period = Percent of Time Heater Burn Average Stack Temp, during Average Oxygen during burn Average Oxygen (Bag) = Total Wood Used = Wood Moisture = AWES Flow Rate = Length of Sample Cycle = Average CO2 (Bag) = Average CO2 (Bag) = Average CO2 (Bag) = TOTAL PARTICULATES: Rinse = XAD-2 = Filter = Average Blank = Total Dry Wood Used = Burn Rate during burn = Average Daily Burn Rate = Alt to Fuel Ratio =	ed = burn = (Stack) = 45,0 n 6.3 n ~30.4 n ~3.9 n	13.5 0.8714 3,0 0.052 0.59 81 19 19 0.017 118.48 7.72	% % % % % % % dy basis with min % % ppro g dry kg dry kg/hr dry kg/hr dy kg/hr
	PARTICULATE EMISSIONS  9/kg 9/kr Ave. daily g/hr=	1.90 14.85	± ±	4.67
	GO EMISSIONS:  g/kg g/hr Ave, daily g/hr=  VOC EMISSIONS:  g/kg	9.57		
	g/hr Ava. dally g/hr≍ ADDITIONAL ITEMS;	73.65 6.53		
	Average Wood Load = Average Wood Usage = Number of times Loaded per to Average Ambient Temperature NET EFFICIENCY:	Day = e =:	41,84 41,84 1,00 75,42	wet lt/day
	Combustion Efficiency =		94.13 68.42 62.53 8105	%

Science Applications International Corporation

10



Page 52 of 72

Attachment 14: Reference G - Report Cover Page



## Evaluation of Efficiency and Emissions from a Moberg/Royal Crown MRC-3036 Masonry Heater

SUMMARY REPORT. Complete report with Appendices available by request to: FireSpaces, Inc. 921 S.W. Morrison St., Suite 440 Portland, Oregon 97205 tel. (503) 227-0547

Prepared for:

Fire Spaces, Inc.
Walter Moberg Design
921 SW Morrison, Suite 440
Portland, Oregon 97205

(503)227-0547

Prepared by:

OMNI Environmental Services, Inc. 5465 SW Western Avenue, Suite M Beaverton, Oregon 97005 (503)643-3788

> May 28, 1994 OMNI REPORT #0015-013

Attachment 14: Reference G - Summary Page

## **Emissions Results**

Table 1 shows the results of AES measurements and sampling over the test period. Total particulate (TP) emissions averaged 3.9 g/kg and 3.4 g per hour. The 95% confidence limit for the g/kg value is ±0.90 g/kg. The average burn rate was 0.88 dry kg/hr.

Average CO emissions were 20.3 g/kg, 17.8 g per hour.

Comparatively, the particulate emissions (Figure 3) were between the emissions of certified pellet stoves as tested in homes<sup>5</sup> and EPA 1990-certified Phase II noncatalytic woodstoves. The Moberg/Royal Crown Model MRC-3036 Masonry Heater emissions are 30% of the EPA's AP-42 emissions value of 14.9 g/kg for conventional woodstoves.

CO emissions are very low as compared to EPA certified catalytic and noncatalytic woodstoves as well as other masonry heaters.

## **Efficiency Results**

The average net delivered efficiency of the Moberg/Royal Crown Model MRC-3036 Masonry Heater was 53.8%. The average heat output was 9372 BTU/hr.

Attachment 15: Reference H1 - Report Cover Page



## Moberg 3042 Masonry Heater Emissions Testing Report

(Compliance with Colorado Regulation No. 4)

Prepared for:

FIRESPACES, INC.

223 NW NINTH AVENUE PORTLAND, OREGON 97209-3305

(503) 227-0547

Prepared by:

OMNI Environmental Services, Inc. 5465 SW Western Avenue, Suite M

Beaverton, Oregon 97005

(503)643-3788

Test Date:

November, 1995

January, 1996 OMNI REPORT #001-S-02-3-8 Attachment 15: Reference H1 – Summary Page

# Masonry Heater EmissionsTesting Report Moberg 3042

Demonstration of Compliance with Colorado Regulation 4 Standards

### **Summary of Testing:**

Starting on November 16, 1995, OMNI Environmental Services, Inc. conducted a two-day emissions test at a private residence in Portland, Oregon for the purpose of obtaining "approved" designation from the Colorado Department of Health for the MRC 3042 masonry heater design. Testing was conducted using an automated sampling system (an OMNI ESS) to determine particulate and carbon monoxide emission factors and to record flue temperature and oxygen concentration data.

#### Test Results and Discussion:

The test results show an average particulate emission factor of 1.95 grams per kilogram (g/kg), at an emission rate of 4.70 grams per hour (g/hour). Carbon Monoxide (CO) emissions were measured at 14 g/kg and 33 g/hour. Testing was conducted as an abbreviated test series in support of Section IV.B.3 of Regulation 4 of the Colorado Air Quality Control Commission (1994). The MRC 3042 fireplace design has substantially the same core construction as the MRC 3036 fireplace (Masonry Heater Approval letter from Gary Finiol; CAQCC, dated August 23, 1994) with modifications only in proportional dimension. The MRC 3042 fireplace design demonstrated particulate emissions that are within the Colorado Regulation 4 requirement of 6.0 g/kg.

Drawings providing dimensions for Regulation 4 Masonry-heater specifications are contained in Appendix G to this report. The following provides a listing of Appendices and their contents:

Attachment 15: Reference H2 - Report Cover Page



## Moberg 3042 Fireplace Heater Emissions Testing Report

(Compliance with Washington State UBC Section 31-2)

SUMMARY REPORT. Complete report with Appendices available by request to:

FireSpaces, Inc.

23 NW Ninth Avenue
Portland, Oregon 97209(503) 227-0547 tel or 227-0548 fax

www.firespaces.com

Prepared for:

FireSpaces, Inc. 223 NW Ninth Avenue Portland, Oregon 97209-

Prepared by:

OMNI Environmental Services, Inc.

5465 SW Western Avenue, Suite M

Beaverton, Oregon 97005

(503)643-3788

Test Date:

November, 1995

January, 1996 001-S-02-3-A Attachment 15: Reference H2 - Summary Page

## Fireplace Heater EmissionsTesting Report Moberg 3042

For Demonstrating Compliance with the Washington State Building Code Standard for Fireplace Emissions Requirements (UBC Section 31-2)

### Summary of Testing:

On November 30, 1995, OMNI Environmental Services, Inc. conducted emissions testing on the MRC 3042 fireplace design in conformance with the Washington State test and operating protocol. The testing reported here was conducted at the Moberg R&D facility in Portland, Oregon. OMNI used the Washington emissions sampling system (an OMNI ESS) to sample particulate emissions. OMNI technician Jacob Tiegs conducted all testing including set-up, take-down, and the laboratory analysis of ESS samples.

Testing was conducted with the doors closed and a hearth grate in place. The fuel loading schedule, load weight, and fuel moisture were determined in accordance with the Washington required protocol. Three fuel charges were loaded during the test period and the unburned ashes were weighed and subtracted at the end of the test period for a total "fuel burned" weight.

## Test Results and Discussion:

The test results show an average particulate emission factor of 1.79 grams per kilogram (g/kg), at an average emission rate of 5.53 grams per hour (g/hour). Carbon Monoxide emissions were measured at 48 g/kg and 148 g/hr. The MRC 3042 fireplace design exhibited emissions that are within the Washington State requirement of 7.3 g/kg.

Table 1 presents a complete summary of test measurements and sample analyses. Figure 1 presents a time-base graph of flue-gas temperatures and oxygen concentrations and indications of when and how much fuel was added during the test period.

Attachment 16: Reference I - AP-42 Revision Report Excerpts

# REPORT ON REVISIONS TO 5TH EDITION AP-42

Section 1.10

Residential Wood Stoves

#### Prepared for:

Contract No. 68-D2-0160, Work Assignment 50
EPA Work Assignment Officer: Roy Huntley
Office of Air Quality Planning and Standards
Office of Air and Radiation
U. S. Environmental Protection Agency
Research Triangle Park, North Carolina 27711

Prepared by:

Eastern Research Group Post Office Box 2010 Morrisville, North Carolina 27560

July 29, 1996

### Attachment 16: Reference I - AP-42 Revision Report Excerpts

#### 4.2.3 References 9 and 10 - Preliminary Data on Wood Stoves

During the winter of 1991-1992, two separate series of in-home emissions tests were conducted on wood stoves in Crested Butte (two noncatalytic Phase II stoves, six catalytic Phase I and two catalytic Phase II stoves) and Klamath Falls (four conventional stoves, three noncatalytic Phase II stoves and two catalytic Phase II stoves). The results of these tests are important in that these stoves have been tested in prior years (excluding the Klamath Falls conventional wood stoves) and the results should provide some insight into the effect of stove degradation on emissions. Degradation mainly affects catalytic components. However, over time, warpage of other internal parts can cause leaks which contribute to increased emissions. Results of these two tests are summarized in Table 4-2, even though the data cannot be included in emission factor development pending evaluation of the test reports. A preferred approach for tracking degradation might be to extract from the existing data base any emissions data for stoves with test results from multiple years, and add in the most recent year's data to form a separate "degradation" data base. In fact, work has already begun to develop this type of data base.

#### 4.2.4 References 11, 13, 13, 14, 15 - Masonry Heaters

References 11 through 15 reported emissions from five types of masonry heaters under in-home burning conditions. All five references reported PM, CO and CO<sub>2</sub> emissions. These data were rated "A." A summary of the test data from all five test series is shown in Table 4-3.

Reference 11 also reported emissions for a "Russian" style masonry heater which was constructed by a mason from a plan that was later changed. Emissions from this unit were not included in the emission factor development since this unit is not commercially available and is probably not representative of the general masonry heater population in terms of construction or emissions.

### Attachment 16: Reference I - AP-42 Revision Report Excerpts

TABLE 4-3. SUMMARY OF NEW IN-HOME EMISSIONS DATA FOR MASONRY HEATERS<sup>11-15</sup>

1 - 1992 s Fir, Alder
s Fir, Alder
19%
.1 hours
41
dry kg/hr
8 g/kg
.5 g/kg

a. These data were collected using an AWES unit, and have been converted to M5H equivalent values. See section 4.3.1.1 of this report for an explanation of the conversion calculations, and Appendix A for a sample calculation.

#### 4.3 EMISSION FACTOR METHODOLOGY

A Lotus 1-2-3<sup>™</sup> spreadsheet was used to compile PM and CO emissions data and calculate emission factors as part of the 1991 revision to the AP-42 section on residential wood stoves. The 1991 spreadsheets were updated during the current revision to include new correlation equations used to calculate equivalent EPA Method 5H values for PM from field-test data. (See section 4.3.1.1 for details of these calculations). New spreadsheets were developed to calculate PM, CO and speciated organic compound emission factors from new references. Also, new spreadsheets were developed to calculate emission factors for noncriteria pollutants (i.e., CO₂ and PAH).

#### 4.3.1 Criteria Pollutant Emission Factor Development

Emission factors for NO<sub>x</sub> (rated "E"), SO<sub>x</sub> (rated "B"), were not changed from the 1991 emission factors. Emission factors for CO and PM were revised using existing emission factors (rated "B") and new data (rated "A") resulting in new composite CO and PM emission factors,

### Attachment 16: Reference I - AP-42 Revision Report Excerpts

TABLE 1.10-2. (METRIC UNITS) EMISSION FACTORS FOR RESIDENTIAL.

		Woo	D COMBUS	STION			
Pollutant/ EPA Certification <sup>b</sup>	Emission Pactor	Wo	odStove Ty	pe <sup>e</sup>	Pellet Stove Type <sup>6</sup>		Masonry Heater
	Rating	Comv. g/kg	Non-Cat g/kg	Cat g/kg	Certified g/kg	Exempt g/kg	Exempt g/kg
<u>PM-10<sup>fg</sup></u>							
Pre-Phase I	В	15.3	12.9	12.1			
Phase 1	В		10.0	9.8			
Phase II	В		73	8.1	2.1		
A11	В	15.3	9.8	10.2	2.1	4.4	2.8
Carbon Monoxidef							
Pre-Phase I	В	115 <i>A</i>					
Phase I	В			52.2			
Phase II	В		70.4	53.5	19.7		
All	В	115.4	70.4	52.4	19.7	26.1	74.5
Nitrogen Oxides		1.44		$1.0^{i}$	6.9 <sup>i</sup>		
<u>Sulfin Oxides</u> f	В	0.2	0.2	0.2	0.2		
Carbon Dioxide	С				1,475.8	1,835.6	1,924.7
Total Organic Compounds							
Methane	E	32.0		13.0			
Non-Methane	E	14.0		8.6	•		

- Units are in (grams of pollutant/kg of dry wood burned).
- b. Pre-Phase I = not certified to 1988 EPA emission standards; Phase I = certified to 1988 EPA emission standards; Phase II = certified to 1990 EPA emission standards; All = average of emission factors for all devices.
- c. Conv = Conventional; Non-Cat = Noncatalytic; Cat = Catalytic.
- d. Certified = Certified pursuant to 1988 NSPS; Exempt = Exempt from 1988 NSPS (i.e., air:fuel ratio >35:1).
- e. Exempt = Exempt from 1988 NSPS (i.e., weight >800 kg).
- f. References 5-13, 22-26, 28.
- g. Defined as equivalent to total catch by EPA method 5H train.
- h. Rating = C.
- i. Rating = E.
  - References 12, 22-26, 28.
- k. References 14, 15, 18. The data used to develop the emission factors showed a high degree of variability within the source population. The use of these emission factors on specific sources may not be appropriate.

10/92 1.10-5

Attachment 17: Reference J1 and J2 - Report Cover Page

	Record
Copy Number:	
Vame	Date

Test Report: Masonry Heater Particulate Emissions and Overall Thermal Efficiency. Tulikivi Oy Model KTU-2100 May 1997

Prepared for:

Tulikivi Oy FIN-83900 Juuka FINLAND

Prepared by:

OMNI-Test Laboratories, Inc. 5465 SW Western Avenue, Suite G Beaverton, Oregon 97005 USA

(503)643-3788

May 1997 Project # 020-S-01-3

All data and information contained in this report are confidential and proprietary to Tulikivi Oy. The contents of this report cannot be copied or quoted, except in full, without specific, written authorization from OMNI-Test Laboratories, Inc. or Tulikivi Oy.

### Attachment 17: Reference J1 and J2 - Summary Page

 Tulikivi Oy. Model KTU-2100
 Test Report

 FINLAND
 Test Paies: May 20 and 21, 1997

#### SUMMARY

The Tulikivi Model KTU-2100 masonry heater was tested for particulate emissions and overall thermal efficiency by OMNI-Test Laboratories, Inc. (OMNI) of Beaverton, Oregon, USA. Two tests were conducted in accordance with the emissions and thermal efficiency sampling and analysis specifications of the Model Performance Standard for Fireplaces and Masonry Heater Emissions: the first one was conducted on May 20, 1997 and the second on May 21, 1997.

Test-Burn Number 1 was conducted using three successive fuel loads of the size and weight stipulated by the Model Standard and the Washington State Method. Test-Burn Number 2 however, was conducted using only one, large fuel load simulating Colorado Regulation-4's in-home user defined fuel loading protocol. The tested masonry heater configuration and test results are presented in the following Summary Table:

Summary Table. Test Configuration and emissions results for the Tullkiyi KTU-2100 Masonry Heater

	140001717216	1-2100 Masonry Heat	SI-	
Test-Burn	Test Configuration	Particulate i		Overall Thermai Efficiency
Number 1 Three fuel load test)	No Lingit Inducer,	2.5 grams/kilogram (U.S. EPA Method 5H equivalents calculated in accordance with Washington State UBC Chapter 31-2)	3.0 grams/hour (per kilogram/hour) (U.S. EPA 5H equivalents calculated in accordance with The Model Standard)	52.5%
Number 2 (Single, large fuel load test)	Door Closed, With Hearth Grate, No Draft Inducer, and No Catalyst	3.1 grams/kilogram (U.S. EPA Method 5H equivalents calculated in accordance with Washington State UBC Chapter 31-2)	3.8 grams/hour (per kilogram/hour) (U.S. EPA 5H equivalents calculated in accordance with The Model Standard)	51.2%

OMNI-Test Laboratories Inc.

Attachment 18: Reference K - Report Cover Page



### Tulikivi Oy; Model TU 1000 **Emissions Testing Report**

(Protocol Conformance with Colorado Regulation No. 4)

Prepared for:

Tulikivi Oy

FIN-83900 Juuka, Finland

Prepared by:

OMNI Environmental Services, Inc. 5465 SW Western Avenue, Suite G

Beaverton, Oregon 97005 (503) 643-3788

April 29, 1999 020-8-06-3

All data and information contained in this report are confidential and proprietary to Firespaces, Inc. The contents of this report cannot be capled or quoted without specific, written authorization from Firespaces, inc.

Attachment 18: Reference K - Summary Page

#### Fireplace Heater Emissions Testing Report Tulikivi TU 1000

For Demonstrating Compliance with the Colorado Regulation 4 Standards

#### Summary of Testing:

Beginning on April 5 and ending on April 12, 1999, OMNI Environmental Services, Inc. conducted "in field" emissions testing on the Tulikivi TU 1000 fireplace design in conformance with the Colorado Regulation 4 Standards and operating protocol. All testing reported here was conducted at the Bullard residence in the rural area east of Livingston, Montana. OMNI used an EPA audited procedure which requires the use of an EPA audited automated wood emissions sampler (an OMNI AWES) to sample particulate emissions. OMNI technician Chuck Fisher conducted all testing including set-up, takedown, data reduction, and the laboratory analysis of samples.

Testing was conducted with the doors closed and a bearth grate in place. The fuel loading schedule for the testing was determined by the home owner. Fuel loading weight was approximately 80% of the manufacturer's recommendations and measured by an OMNI technician. Fuel moisture content was measured by an OMNI technician. One load of fuel was burned per day.

#### Test Results and Discussion:

The test results show an average particulate emission factor of 2.6 grams per kilogram (g/kg). The Tulikivi; Model TU 1000 design exhibited emissions that meet the emission standards set forth in Federal Regulations 40CFR Part 60, Subpart AAA, Subsection 60.532(b)(1) or (2). The resulting average particulate emission factor is below the Colorado State requirement of 6.0 g/kg.

Table 1 presents a summary of test measurements and sample analyses for the test. Plot 1 presents a time-base graph of flue-gas temperatures, flue-gas oxygen concentrations, and indications of when and how fuel was added during the test period.

Attachment 19: Reference L - Report Cover Page



Tulikivi Oy; Model TU 2200 Emissions Testing Report

(Protocol Conformance with Colorado Regulation No. 4)

Prepared for:

Tulikivi Oy

FIN-83900

Junka, Finland

Prepared by:

OMNI Environmental Services, Inc.

5465 SW Western Avenue, Suite G

Beaverton, Oregon 97005

(503) 643-3788

April 29, 1999 020-S-06-3

All data and information contained in this report are confidential and proprietary to Firespaces, Inc. The contents of this report connot be copied or quoted without specific, written authorization from Firespaces, Inc.

Attachment 19: Reference L - Summary Page

#### Fireplace Heater Emissions Testing Report Tulikivi TU 2200

For Demonstrating Compliance with the Colorado Regulation 4 Standards

Summary of Testing:

Beginning on April 5 and ending on April 12, 1999, OMNI Environmental Services, Inc. conducted "in field" emissions testing on the Tulikivi TU 2200 fireplace design in conformance with the Colorado Regulation 4 Standards and operating protocol. All testing reported here was conducted at the McGee residence within the city limits of Livingston, Montana. OMNI used an EPA audited procedure which requires the use of an EPA audited automated wood emissions sampler (an OMNI AWES) to sample particulate emissions. OMNI technician Chuck Fisher conducted all testing including set-up, takedown, data reduction, and the laboratory analysis of samples.

Testing was conducted with the doors closed and a hearth grate in place. The fuel loading schedule for the testing was determined by the home owner. Fuel loading weight was approximately 80% of the manufacturer's recommendations and measured by an OMNI technician. Fuel moisture content was measured by an OMNI technician. One load of fuel was burned per day.

#### Test Results and Discussion:

The test results show an average particulate emission factor of 3.5 grams per kilogram (g/kg). The Tulikivi; Model TU 2200 design exhibited emissions that meet the emission standards set forth in Federal Regulations 40CFR Part 60, Subpart AAA, Subsection 60.532(b)(1) or (2). The resulting average particulate emission factor is below the Colorado State requirement of 6.0 g/kg.

Table I presents a summary of test measurements and sample analyses for the test. Plot I presents a time-base graph of flue-gas temperatures and the flue-gas oxygen concentrations.

Attachment 20: Reference M - Report Cover Page



### Tulikivi Oy; Model TLU 2450 Emissions Testing Report

(Protocol Conformance with Colorado Regulation No. 4)

Prepared for:

Tulikivi Oy FIN-83900

Juuka, Finland

Prepared by:

OMNI Environmental Services, Inc. 5465 SW Western Avenue, Suite G

Beaverton, Oregon 97005

(503) 643-3788

April 29, 1999 020-\$-06-3

All data and information contained in this report are confidential and proprietary to Firespaces, Inc. The contents of this report cannot be copied or quoted without specific, written authorization from Firespaces, Inc.

Attachment 20: Reference M - Summary Page

#### Fireplace Heater Emissions Testing Report Tulikivi TLU 2450

Por Demonstrating Compliance with the Colorado Regulation 4 Standards

#### Summary of Testing:

Beginning on April 5 and ending on April 12, 1999, OMNI Environmental Services, Inc. conducted "in field" emissions testing on the Tulikivi TLU 2450 fireplace design in conformance with the Colorado Regulation 4 Standards and operating protocol. All testing reported here was conducted at the residence Dr. Sirr in the rural are north of Gardiner, Montana. OMNI used an EPA audited procedure which requires the use of an EPA audited automated wood emissions sampler (an OMNI AWES) to sample particulate emissions. OMNI technician Chuck Fisher conducted all testing including set-up, takedown, data reduction, and the laboratory analysis of samples.

Testing was conducted with the doors closed and a hearth grate in place. The fuel loading schedule for the testing was determined by the home owner. Fuel loading weight was approximately 80% of the manufacturer's recommendations and measured by an OMNI technician. Fuel moisture content was measured by an OMNI technician. One load of fuel was burned per day.

#### Test Results and Discussion;

The test results show an average particulate emission factor of 2.0 grams per kilogram (g/kg). The Tulikivi; Model TLU 2450 design exhibited emissions that meet the emission standards set forth in Federal Regulations 40CFR Part 60, Subpart AAA, Subsection 60.532(b)(1) or (2). The resulting average particulate emission factor is below the Colorado State requirement of 6.0 g/kg.

Table 1 presents a summary of test measurements and sample analyses for the test. Plot 1 presents a time-base graph of flue-gas temperatures and the flue-gas oxygen concentrations.

Attachment 21: Reference N1 and N2 - Report Cover Page



# **Emissions Report**

# Swedish Kakelugn Style Masonry Heater Built by: Jerry Frisch

OMNI-Test Laboratories, Inc. Product Testing & Certification

Mailing: Post Office Box 743 Street: 5485 SW Wastern Avenue • Suite G

Beaverton, Oregon 97075 USA

(503) 643-3788 (503) 643-3799

OMNI-Test Laboratories, Inc. Yea Report devid Oxeder 2007: Immire were france Marchy Research me my

10/4

### Attachment 21: Reference N1 and N2 - Summary Page

OMNI-Test Laboratories, Inc has completed a series of emissions tests on the Swedish Kakelugn style masonry heater built by Jerry Frisch. The appliance cured for 20 days before testing was initiated.

OMNI performed a total of 8 tests on the masonry heater, 4 with dimensional lumber and 4 with cordwood. Testing began on July 12, 2006 and concluded on August 14, 2006. The fueling protocol used was the Colorado Masonry Heater Standard using dimensional lumber. The emissions were sampled using 3 different sampling systems:

- The proposed ASTM dilution tunnel sampling system that uses dual 47mm filter trains. This system is very similar to the U.S.
   Environmental Protection Agency Method 5G-3.
- Samples were also taken using the Emission Sampling System (ESS) developed by OMNI in the late 1980's for the U.S. EPA for performing in situ, in-home testing of wood-fired fireplace and home heating appliances.
- 3. On tests 5 & 6, the Condar emissions sampling system was also used.

The results of all of the tests performed are shown in Table 1.

Table 1

Run	Fuel Moisture (dry basis)	Fuel Weight (dry kg)	Test Duration (hours)	Burn Rate (dry kg/hr)	Emissions Factor (g/kg) ASTM	Emissions Factor (g/kg) ESS	Emissions Factor (g/kg) Condar	Fuel Type
1	20.9	16.3	5.3	3.1	3.3	2.1	Not tested	Dimensional
2	11.7	18.8	5.0	3.8	2.7	1.9	Not tested	Cordwood
3	23.0	17.0	5.2	3.3	5.0	2.3	Not lested	Dimensional
4	10.9	19.0	4.7	4.1	2.7	2	2.5	Cordwood
5	20.9	18.0	6.0	3.0	2.7	2	2.5	Dimensional
6	22.3	16.7	5.3	3.1	2.3	1.7	Not tested	Dimensional
7	11.9	21.5	5.3	4.0	2.4	2	Not tested	Cordwood
8	10.9	19.3	5.0	3.9	2.9	2	Not lested	Cordwood

OMNI-Test Laboratories, Inc. Test Report duck (Journe 1027) - commissions to study Marriery Heater sees repor